

AV Bridge – Wireless Control Integration Module



- Enables the use of Crestron® battery-powered wireless AV keypads with a Crestron control system
- Allows Zūm® occupancy and vacancy sensors to be used in non-Zūm applications
- Facilitates basic control of an AirMedia® Presentation System¹
- Connects the keypads and sensors to a control system or computer
- Interfaces a complete Zūm commercial lighting system with a local AV control system
- Choice of RS-232 or USB interface
- Simple, brand-agnostic command set
- Zūm Mesh peer-to-peer wireless technology
- Ultra-compact, surface mount design
- 12-24 VDC or USB powered

The AV Bridge ([ZUMMESH-AVBRIDGE](#)) is a wireless control integration module designed for use with Crestron® Battery-Powered Wireless AV Keypads ([ZUMMESH-KPAVBATT](#)) and Zūm® Wireless Battery-Powered Occupancy and Vacancy Sensors ([ZUMMESH-PIR-OCCUPANCY-BATT](#) and [ZUMMESH-PIR-VACANCY-BATT](#)). It enables simple control of AV and other functions by connecting the keypads and sensors to a control system, computer, or Crestron AirMedia® Presentation System device.¹ A simple, brand-agnostic command set allows for integration with both Crestron and third-party systems via RS-232 or USB.² The AV Bridge pairs wirelessly with up to eight keypads and eight sensors in a room without requiring a separate wireless gateway.³

AV Control System Integration, Control, and Monitoring

The AV Bridge allows a Zūm commercial lighting system to integrate with an AV control system. Connecting the systems enables bi-directional control and monitoring between the Zūm Mesh wireless devices in a Zūm commercial lighting system and the components in the AV control system.

Surface Mount

The Zūm AV Bridge is designed to be mounted to a wall or other flat surface. Care should be taken when positioning the device to avoid interference from nearby RF devices, obstructions, and metal surfaces.

AV Bridge – Wireless Control Integration Module

Specifications

Wireless Communications

RF Transceiver:	Zūm Mesh 2-way RF, 2.4 GHz ISM Channels 15, 20, 25, or 26 (channel auto-selected), IEEE 802.15.4 compliant, AES-128 encryption
Range:	50 ft (15 m) to nearest peer-to-peer mesh network device(s), subject to site-specific conditions and individual device capabilities ³

NOTE: A maximum of 32 Zūm Mesh wireless devices is permitted per room inclusive of a maximum of 8 battery-powered keypads and 8 occupancy or vacancy sensors.

Wired Communications

RS-232:	2-way serial up to 115.2k baud (TD/RD only)
USB:	USB 1.1, appears as a virtual COM port on the host computer

Connectors

COM:	(1) 3-pin 3.5 mm detachable terminal block; Bidirectional RS-232 port
COMPUTER:	(1) USB Type Micro-B connector, female; USB 1.1 device port ⁴ ; 3 ft (0.91 m) USB micro-B male to A male cable included
PWR 12-24 VDC:	(1) 2-pin 3.5 mm detachable terminal block; 12-24 VDC power input

Controls and Indicators

PWR:	(1) Bi-color LED; Amber indicates device is booting; Green indicates device is operating
NET:	(1) Amber LED; Indicates Zūm Mesh wireless network activity
TX:	(1) Green LED; Indicates serial data transmission
RX:	(1) Green LED; Indicates serial data reception
ERR:	(1) Red LED; Indicates an error condition
SETUP:	(1) Red LED and (1) recessed pushbutton; For room setup and factory reset

Power

Power Options:	12-24 VDC or USB ⁴
Power Consumption:	1 W

Environmental

Temperature:	32° to 113°F (0° to 45°C)
Humidity:	10% to 90% RH (noncondensing)
Heat Dissipation:	3 BTU/hr

Construction

Plastic, black, (2) integral surface mounting flanges, vented sides

Dimensions

Height:	0.69 in. (18 mm)
Width:	2.58 in. (66 mm)
Depth:	2.49 in. (64 mm)

Weight

1.6 oz (45 g)

Compliance

IC, FCC Part 15 Class B digital device

Models

ZUMMESH-AVBRIDGE

Available Accessories

PW-2407RU
18 W Cresnet® Power Supply, US/International

CNSP-XX
Custom Serial Interface Cable

ZUMMESH-KPAVBATT Series
Battery-Powered Wireless AV Keypad

ZUMMESH-PIR-OCCUPANCY-BATT
Zūm® Wireless Battery-Powered Occupancy Sensor

ZUMMESH-PIR-VACANCY-BATT
Zūm® Wireless Battery-Powered Vacancy Sensor

ZUMMESH-KPAMBATT Series
AirMedia® Wireless, Battery-Powered Keypad

AV Bridge – Wireless Control Integration Module

Notes:

1. Use RS-232 for connection to a Crestron control system. Use USB for connection to a Crestron AirMedia® Presentation System device. When connected to a computer via USB, the interface appears as a virtual COM port. Connecting the USB port to any USB host disables the RS-232 port. Custom commissioning is required when integrating with a control system. Custom software is required when integrating with a computer.
2. The ZUMMESH-AVBRIDGE uses "Züm Mesh" wireless technology to connect and communicate with the keypads, sensors, and lighting devices. Züm Mesh is a peer-to-peer wireless mesh network designed to operate within a single room. The ZUMMESH-AVBRIDGE and all AC-powered Züm Mesh devices function as routing nodes, which effectively extend the range of the wireless network within the room. Battery-powered devices only function as leaf nodes and do not extend range. Networks composed predominantly of battery-powered devices may require additional AC-powered devices, such as the ZUMMESH-JBOX-PSU, to serve as supplemental routing nodes to fill any gaps in coverage. Refer to the "Installation and Setup of Crestron RF Products, Best Practices" guide (Doc #6689) for additional guidelines.
3. Power supply not included. Connecting the USB port to a USB host disables the RS-232 port.
4. Compatible with AM-200, AM-300, AM-3000-WF(-I), AM-3100-WF(-I), AM-3200, AM-3200-WF(-I), AM-3200-GV AirMedia Presentation Systems.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, AirMedia, Cresnet, and Züm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2019 Crestron Electronics, Inc.

Rev 09/10/19

AV Bridge – Wireless Control Integration Module

