

Cameo® In-Wall Dimmer/Switch Combo, 120V



- Provides forward-phase dimming and switch control
- Field replaceable and engravable buttons
- Configurable up to 4 buttons
- LED bargraph array provides real-time status feedback
- Available in a variety of finishes
- Modeled with popular Cameo® keypad style
- Robust infiNET EX® wireless communication
- Crestron Home® OS compatible
- Screw clamp connectors for easier & improved installation

The CLW-DIMSWEX-P is a Cameo® wireless in-wall combination dimmer/switch which features field-replaceable and engravable buttons. Along with the entire line of Cameo products, it can be configured with various button layouts and designer colors, making the CLW-DIMSWEX-P more versatile and affordable than previous generations of in-wall dimmers. Able to dim one load and switch another simultaneously, the CLW-DIMSWEX-P dimmer/switch is great for applications needing to control a fan and light from a single gang in the wall. Its streamlined design matches the entire line of Cameo dimmers, switches and keypads, making it a great addition to new or retrofit installations. In addition, infiNET EX® wireless communication technology brings proven reliability to the CLW-DIMSWEX-P.

Dimmer and Switch in a Single Gang

Easily control two independent loads from the single gang CLW-DIMSWEX-P. Designed to reduce wall clutter in new installations and replace existing dual-switch combos in retrofit situations, the Cameo dimmer and switch combo lets you bring controlled lighting to more rooms. Perfect for bathrooms, the CLW-DIMSWEX-P lets you switch on the exhaust fan and dim the lights with one button press. The fan can also be set to run for a set period of time after being activated.

Field-Replaceable and Engravable Buttons

The buttons on the CLW-DIMSWEX-P can be swapped in the field, making it easy to change the engraving or color after installation. The rocker controller brings an easy to utilize user interface to the Crestron in-wall dimmer. Use up to 4 buttons to take advantage of prime single-gang wall box real estate; buttons can control in-room audio or lamps in addition to any other light connected to the system. The comprehensive list of designer colors blends the CLW-DIMSWEX-P into any décor and style, suiting every space.

Custom Programmable Keypad

Because the CLW-DIMSWEX-P is attached to the Crestron network, it also functions as a keypad, sending commands to trigger whole-room scenes or distributed audio functions. Supporting up to four buttons, the in-wall dimmer serves as a great user control interface in any Crestron system. Its single-gang form factor maximizes control capability in a small space while increasing the opportunity for Crestron control in every room.

infiNET EX® Wireless Communications

infiNET EX wireless technology provides two way RF communications throughout a residential or commercial structure without the need for physical control wiring. Each infiNET EX device acts as an expander by sending command signals to other infiNET EX devices in range (approximately 150 ft (46 m) indoors) to ensure reliability and stability.

The device communicates with a control system via a [Crestron Wireless Gateway](#) (sold separately). Up to 100 infiNET EX devices may coexist on a wireless network.

NOTE: Any infiNET EX device that provides expander functionality will effectively extend the range of the wireless network beyond the initial range of the gateway. Battery-powered infiNET EX devices do not provide expander functionality. A dedicated infiNET EX Wireless Expander is also available ([CLW-EXPEX](#), sold separately).

Streamlined Installation

The CLW-DIMSWEX-P features screw-clamp connectors for simplified wiring, reducing installation time and material costs. The Cameo line can be installed in standard gang boxes making them the perfect choice for both new and retrofit projects.

Multigang Expansion

Devices can be installed side-by-side in a multigang electrical box with a compatible decorator faceplate ([FP-G Series](#), sold separately).

Cameo® In-Wall Dimmer/Switch Combo, 120V

Specifications

Load Requirements (Dimmer)

Incandescent/Tungsten Halogen, Magnetic Low Voltage, Dimmable CFL	500VA/W
Minimum Load	25 W

Load Requirements (Switch)

Exhaust Fan	1A
-------------	----

Power Requirements

120VAC, 60 Hz, line power

Controls

Button 1-4	Configurable for 1 to 4 single-action pushbuttons, programmable via control system
------------	--

LED Indicator

Feedback	(7) White LEDs
Bargraph	(1) 7 segment bargraph display utilizing the 7 feedback LEDs

Wireless

RF Transceiver	infiNET EX® 2-way RF, 2.4 GHz ISM Channels 11-26 (2400 to 2483.5 MHz), default channel 15; IEEE 802.15.4 compliant
Range (typical)	150 ft (46 m) indoor, 250 ft (76 m) outdoor to nearest mesh network device(s); Subject to site-specific conditions and individual device capabilities
Gateway	Requires a Crestron Wireless Gateway (sold separately)

Connections

Hot	(1) 14-12 AWG, screw terminal, brass, line power input
Dim	(1) 14-12 AWG, screw terminal, red, dim load output
Switch	(1) 14-12 AWG, screw terminal, red, switch load output
Neutral	(1) 14-12 AWG, screw terminal, silver, neutral; Neutral wire connection is required for normal operation
Ground	(1) 16 AWG Class 1 flying lead, green, ground

Environmental

Temperature	32° to 104°F (0 °to 40°C)
Humidity	10% to 90% RH (noncondensing)

Construction

Mounting	1-gang mountable in a 3-1/2 in. deep electrical box; Derating required in multigang applications
Faceplate	Requires a decorator style faceplate (FP-G Series , sold separately).

Dimensions

Height	4.13 in. (105 mm)
Width	1.75 in. (45 mm)
Depth	1.75 in. (45 mm)

Weight

4.9 oz (139 g)

Compliance

Regulatory Model: CLW-DIMSWEX-P

FCC Part 15 Class B, UL® Listed for US and Canada, CEC Title 24 2013 Compliant

To search for product certificates, refer to support.crestron.com/app/certificates.

Models

CLW-DIMSWEX-P-A-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Almond Smooth

CLW-DIMSWEX-P-A-T

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Almond Textured

CLW-DIMSWEX-P-BRN-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Brown Smooth

CLW-DIMSWEX-P-B-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Black Smooth

CLW-DIMSWEX-P-B-T

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Black Textured

CLW-DIMSWEX-P-DA-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Dark Almond Smooth

Cameo® In-Wall Dimmer/Switch Combo, 120V

CLW-DIMSWEX-P-DSK-T

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Dusk Textured

CLW-DIMSWEX-P-GRY-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Gray Smooth

CLW-DIMSWEX-P-IVR-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Ivory Smooth

CLW-DIMSWEX-P-LAT-T

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, Latte Textured

CLW-DIMSWEX-P-W-S

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, White Smooth

CLW-DIMSWEX-P-W-T

Cameo® Wireless In-Wall Dimmer/Switch Combo, 120V, White Textured

Available Accessories

For a list of available accessories, visit the [CLW-DIMSWEX-P](#) product page.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at www.crestron.com/warranty.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, Cameo, Crestron Home, and infiNET EX are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2023 Crestron Electronics, Inc.

Rev 08/25/23

Cameo® In-Wall Dimmer/Switch Combo, 120V

