

GL-EXP-SW-DALI

Crestron Green Light® Switch Expansion Module, DALI®

- > Single-channel lighting switch
- > DALI® system interface
- > Supports on/off switching of LED, incandescent, fluorescent, magnetic low-voltage, electronic low-voltage, neon/cold cathode, and high-intensity discharge lighting loads
- > Also supports on/off switching of motor loads
- > Rated 16 Amps at 100-277 Volts AC
- > Built-in air gap relay
- > UL® 924 listed for emergency lighting control
- > Surface mountable NEMA Type 1 enclosure
- > Mounts on a wall panel or above a suspended ceiling
- > UL 2043 listed for installation in an environmental air handling space

The Crestron Green Light® GL-EXP Series delivers a family of professional lighting control modules for Cresnet® or DALI® based lighting systems. Designed for easy installation on a wall or above a suspended ceiling, these modules offer a perfect solution for adding extra lighting zones to any system without requiring an additional lighting cabinet.

The GL-EXP-SW-DALI is a single-channel switch expansion module designed to control a wide range of non-dimmable lighting loads including LED, incandescent, fluorescent, magnetic low-voltage, electronic low-voltage, neon/cold cathode, and high-intensity discharge. It can also be used to switch motor loads.

DALI® Communications

The GL-EXP-SW-DALI communicates using the DALI (Digital Addressable Lighting Interface) standard, which enables interoperability with other DALI compliant lighting control products from Crestron and other manufacturers. Interfacing a network of DALI switches and other devices with a Crestron lighting control system is facilitated using the [DIN-DALI-2](#) (sold separately).

Emergency Lighting Control

The GL-EXP-SW-DALI is UL® 924 listed for use in controlling an emergency lighting load. In the event of a power failure indicated by a loss of DALI network communication (system failure), the GL-EXP-SW-DALI turns on the lighting load if it is off (assuming line power is supplied by a backup power source).

Plenum Rated NEMA Enclosure

The GL-EXP-SW-DALI is designed to be mounted to a vertical surface and is UL 2043 compliant to allow for installation in an environmental air-handling space above a suspended ceiling. Conduit knockouts are provided on the bottom and lower sides of the unit. All connections are made via screw terminals behind the front cover.



SPECIFICATIONS

Load Control

Dimmer Channels: 1

Load Rating: 16 Amps

Line Voltage: 100-277 Volts AC, 50/60 Hz

Switched Load Types: LED, incandescent, fluorescent, magnetic low-voltage, electronic low-voltage, neon/cold cathode, high-intensity discharge (HID), motor

Communications

DALI: DALI control gear, IEC 62386 compliant

Connections

NEUT: (3) Captive screw terminals;
Neutral connections for feed and load;
24 to 10 AWG (0.25 to 4.0 mm²) wire size

LINE: (2) Captive screw terminals;
Line power feed input and pass-through;
24 to 10 AWG (0.25 to 4.0 mm²) wire size

GL-EXP-SW-DALI Switch Expansion Module, DALI®

SW: (1) Captive screw terminal;
Switched load output;
24 to 10 AWG (0.25 to 4.0 mm²) wire size

DALI: (2) Sets of (2) captive screw terminals;
DALI control gear interface ports;
26 to 14 AWG (0.14 to 1.5 mm²) wire size;
For use with Class 2 wiring only

Ground: (1) 3-terminal grounding block

Controls & Indicators

PWR: (1) Green LED, indicates line power is applied to either LINE terminal
NET: (1) Yellow LED, indicates DALI network communication
ERR: (1) Red LED, indicates a variety of error conditions via blinking patterns (refer to the installation guide)
ON/OFF: (1) Pushbutton and (1) red LED, pushbutton toggles the load output on and off, LED indicates the load output is energized
RESET: (1) Pushbutton, initiates hardware reset

Environmental

Temperature: 32° to 104° F (0° to 40° C)
Humidity: 10% to 90% RH (non-condensing)

Construction

Enclosure: NEMA Type 1, galvanized steel with gray matte powder coated removable front cover panel, extruded aluminum heat sink on rear, (2) integral mounting flanges, (4) 1/2" or 3/4" conduit knockouts on bottom and lower left & right sides

Mounting: Surface mount, must be oriented upright and mounted to a vertical surface with 6 inches (153 mm) minimum spacing above and below for proper ventilation and heat dissipation

Dimensions

Height: 8.78 in (223 mm)
Width: 6.39 in (163 mm)
Depth: 3.16 in (81 mm)

Weight

3.43 lb (1.56 kg)

Compliance

C(UL)US, UL 924, UL 2043, IEC 62386, FCC Part 15 Class A commercial use

MODELS & ACCESSORIES

Available Models

GL-EXP-SW-DALI: Crestron Green Light® Switch Expansion Module, DALI®

Available Accessories

DIN-DALI-2: DIN Rail 2-Channel DALI® Interface

Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Crestron Green Light are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. DALI is either a trademark or registered trademark of ZVEI-Zentralverband Elektrotechnik- und Elektronikindustrie e.V. in the United States and/or other countries. UL is either a trademark or registered trademark of UL LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2017 Crestron Electronics, Inc.

GL-EXP-SW-DALI Switch Expansion Module, DALI®

