

## Automation Enclosures



CAEN-7x2 SHOWN WITH AND WITHOUT COVER  
PRODUCTS SHOWN IN ENCLOSURE SOLD SEPERATELY

- Enclosures for CLX Series lighting control modules and Crestron control systems
- Available in six convenient sizes
- Surface or flush wall-mountable
- Built to enable over 100 dimmer-controlled circuits per enclosure
- Support for centralized and distributed system configurations
- Residential and commercial applications
- Quiet and reliable, with efficient convection cooling
- Galvanized steel backbox with grounding blocks, low-voltage partitions, and vented front cover
- Additional mounting and termination accessories available
- For 120 and 230 Volt systems
- Additional uses for non-lighting applications such as voice and data structured wiring, security, and RF signal distribution
- UL® Listed panel shop fabrication service available

The CAEN Series automation enclosures are designed to house the Crestron CLX Series lighting control modules, as well as [DIN-AP4](#) or [DIN-AP4-R](#) control systems. Mounting DIN 4-Series® automation processors and Cresnet® hubs to the CAEN requires a [CAEN-UMP1X2-DIN-PWS](#). CAEN enclosures are available in an assortment of sizes, and are suitable for surface or flush wall-mount installation. Each model has been engineered to provide a clean and manageable installation and has abundant provisions for wire termination and electrical knockouts.

### Efficiently Houses Equipment

CAEN automation enclosures are designed to use space efficiently, supporting over a hundred possible circuits in the largest model. Both centralized and distributed configurations are possible. A single control system installed in a central enclosure can support numerous satellite extension enclosures distributed throughout a residence or commercial facility. Interconnection of the complete network of enclosures requires just one circulating Cresnet® cable. Dozens of keypads, touch screens, wall box dimmers, shade controllers, and other peripherals can also be terminated within an enclosure, with separate compartments provided for high- and low-voltage wiring.

### Cool and Quiet

Crestron lighting and automation systems are completely convection cooled for silent and reliable operation. A vented front cover is included with every enclosure. All models are constructed of 16-gauge galvanized steel and are pre-drilled for mounting CLX Series modules, CLT Series terminal blocks, power supplies, [CAEN-BLOCK-CENCN-2-POE](#) bridges, CAEN-UMP1X2-DIN-PWS mounting kits, and CAEN-BLOCK terminal blocks. Additional non-CLX Series lighting modules and third-party contactors may be installed using Crestron's CAEN-UMP universal mounting plates. Grounding blocks and low-voltage partitions are included.

### Useful in Many Applications

CAEN enclosures are also well suited for all types of Class 2 and Class 3 applications including voice and data structured wiring, security, and RF signal distribution (as permitted by applicable codes).

### UL Listed

CAEN enclosures are UL and C-UL listed. If you require a complete UL Listed panel, Crestron offers this service through its UL Listed panel shop, providing complete in-factory system configuration and assembly.

## Specifications

### Environmental

<b>Temperature</b>	32° to 104°F (0° to 40°C)
<b>Humidity</b>	10% to 90% RH (noncondensing)

### Enclosure

16-gauge galvanized steel backbox with perforated gray steel cover, surface or flush wall-mount installation

### Backbox Dimensions

<b>CAEN-7x2</b>	<b>Height:</b> 62.00 in (157.48 cm)
	<b>Width:</b> 25.50 in (64.77 cm)
	<b>Depth:</b> 4.00 in (10.16 cm)

## Automation Enclosures

<b>CAEN-7X1</b>	<b>Height:</b> 62.00 in (157.48 cm) <b>Width:</b> 14.38 in (36.51 cm) <b>Depth:</b> 4.00 in (10.16 cm)
<b>CAEN-4X2</b>	<b>Height:</b> 38.25 in (97.16 cm) <b>Width:</b> 25.50 in (64.77 cm) <b>Depth:</b> 4.00 in (10.16 cm)
<b>CAEN-4X1</b>	<b>Height:</b> 38.25 in (97.16 cm) <b>Width:</b> 14.38 in (36.51 cm) <b>Depth:</b> 4.00 in (10.16 cm)
<b>CAEN-2X1</b>	<b>Height:</b> 23.50 in (59.69 cm) <b>Width:</b> 14.38 in (36.51 cm) <b>Depth:</b> 4.00 in (10.16 cm)
<b>CAEN-1X1</b>	<b>Height:</b> 16.56 in (42.06 cm) <b>Width:</b> 16.10 in (40.90 cm) <b>Depth:</b> 4.25 in (10.80 cm)

### Weight

<b>CAEN-7x2</b>	65.0 lbs (29.48 kg)
<b>CAEN-7X1</b>	42.0 lbs (19.05 kg)
<b>CAEN-4X2</b>	43.0 lbs (19.50 kg)
<b>CAEN-4X1</b>	28.0 lbs (12.70 kg)
<b>CAEN-2X1</b>	19.0 lbs (8.62 kg)
<b>CAEN-1X1</b>	14.0 lbs (6.35 kg)

### Compliance

UL Listed for US and Canada

### Models

#### **CAEN-7x2**

Automation Enclosure, 7 Modules High x 2 Modules Wide

#### **CAEN-7X1**

Automation Enclosure, 7 Modules High x 2 Modules Wide

#### **CAEN-4X2**

Automation Enclosure, 4 Modules High x 2 Modules Wide

#### **CAEN-4X1**

Automation Enclosure, 4 Modules High x 1 Module Wide

#### **CAEN-2X1**

Automation Enclosure, 2 Modules High x 1 Module Wide

#### **CAEN-1X1**

Automation Enclosure, 1 Module High x 1 Module Wide

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.



The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).


Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.  
©2024 Crestron Electronics, Inc.  
Rev 01/08/24

CAEN-7X2





CAEN-7X1




## Automation Enclosures

CAEN-4X2




## Automation Enclosures

CAEN-4X1



## Automation Enclosures

CAEN-2X1



## Automation Enclosures

CAEN-1X1

