

# DGE-100

## Digital Graphics Engine 100



- *Touch screen graphics engine for the Crestron® TSD-2220 or a third-party USB HID-compliant touch screen*
- *Supports OSM (on-screen menu) applications without a touch screen*
- *HDMI® output supports display resolutions up to Full HD 1080p60 and WUXGA*
- *Displays dual-window or full screen video from HDMI and H.264 streaming sources*
- *Supports video input resolutions up to 1080p60 via HDMI*
- *Receives H.264 streaming video signals up to 1080p60/25 Mbps*
- *HDCP 1.4 compliant (HDMI only)*
- *Supports Smart Graphics® technology custom user projects*
- *Built-in annotation capabilities*
- *Built-in web browsing*
- *Onboard COM, HDMI, IR/serial, and high-speed Ethernet ports*
- *High-speed USB 2.0 port for USB HID-compliant peripheral devices*
- *Powered via PoE or included power pack*
- *Enterprise-grade security and authentication*
- *Web or cloud-based configuration*
- *Compact, surface-mountable form factor*

The Crestron® [DGE-100](#) digital graphics engine transforms an HD touch screen display into an advanced Crestron controller. The DGE-100 features Smart Graphics® technology that may be used to create a custom graphical environment for controlling audio, video, lighting, shades, HVAC, security, and other amenities. The DGE-100 can also be used for functions with dual-window video display, annotation, audio feedback, and web browsing. Its low-profile, surface-mountable design allows for a discreet installation behind a flat-panel display, under a table, or inside a lectern or equipment rack.

The DGE-100 features an HDMI® output for connecting to a display device, and includes a USB HID port for touch, mouse, or keyboard input. Additional control ports are provided for controlling the display device and other equipment. The HDMI input allows an AirMedia® wireless presentation gateway or other high-definition video source to be connected and displayed on-screen. Additionally, H.264 streaming video signals can be received over a high-speed Ethernet connection, and Ethernet provides an interface to a Crestron control system.<sup>1</sup>

### Touch Screen Interface

The DGE-100 can be paired with the [TSD-2220](#) HD touch screen display to deliver a high-definition 21.5 in. touch screen control panel that is ideal for home, corporate, and government applications. The DGE-100 is also compatible with third-party touch screen displays to support a range of control, collaboration, video display, and interactive kiosk solutions.

### OSM Interface

On-screen menu (OSM) capability offers an alternative to touch screen control, providing a fully-customizable control menu on a television or video display. The control menu is easily navigated via a [Crestron handheld remote](#) or a USB mouse. The DGE-100 delivers high-resolution menu graphics that pop up unobtrusively at the edge of the screen alongside the video source. Control functions such as adjusting lighting or lowering shades can be easily performed without interrupting a television program or video stream. Detailed alert messages can be configured to display on-screen for events such as security alarms or a doorbell ring, and a live-streaming camera window can be accessed to check security cameras.

### Smart Graphics Technology

Smart Graphics® technology enables programmers to integrate fluid gesture-driven controls, animated feedback, rich metadata, embedded apps and widgets, and full-motion video into their user interfaces. Smart Graphics provides dynamic features such as graphical buttons and sliders, lists and toolbars, drag-and-drop objects, dashboard widgets, screensavers, and customizable themes.<sup>1</sup>

### HD Streaming Video

The DGE-100 supports high-definition streaming video, making it possible to view security cameras and other video sources over the network via the touch screen display. Native support for H.264 and MJPEG formats allows the DGE-100 to display live streaming video from an IP camera, a streaming encoder ([DM-TXRX-100-STR](#) or similar), or a [DigitalMedia™ switcher](#).<sup>1</sup>

### HDMI Input

An HDMI® input is provided for connecting and displaying an HD video source. Wireless presentation is also supported by connecting an [AirMedia® gateway](#) to the HDMI input, allowing for laptops and mobile devices to connect to the DGE-100 over Wi-Fi® communications.<sup>2</sup>

# DGE-100

## Digital Graphics Engine 100

### HDCP Support

Support for HDCP (High-bandwidth Digital Content Protection) ensures seamless compatibility with content-protected optical disc, television, and streaming sources.

### Web Browsing

Using its built-in web browser, the DGE-100 provides access to online program guides and other web-based services, and it can be used to control DVRs and other devices without having to pick up a separate tablet or smartphone.<sup>3</sup>

### Multitouch Support

When paired with the TSD-2220 or another multitouch compatible touch screen display, the DGE-100 affords enhanced capabilities for browsing web pages using multitouch control.

### On-screen Keyboard

Typing in passwords, URLs, and text searches is facilitated using the on-screen multilanguage keyboard.

### Built-in Annotation

Annotation helps to add another dimension to any presentation. Native to the DGE-100, annotation provides the ability to capture ideas in real time, letting you draw and write over a video source or sketch out thoughts on a whiteboard screen.

Remote annotation capability allows multiple participants, each with a separate touch screen, to annotate over the same video image or whiteboard for enhanced collaboration. Remote annotation is possible by using multiple digital graphics engines and touch screens. Adding a dedicated DGE-100 to the main display in a room allows the annotated session to be viewed by an entire audience.

### Onboard Control Ports

The DGE-100 provides built-in RS-232 and IR ports for programmable control of the connected display and other devices via a control system. When connected to a control system via Ethernet, the DGE-100 offers a gateway for controlling the display device directly through its HDMI connection, which reduces the need for any dedicated serial cables or IR emitters. Additional control capabilities are available by using CEC (Consumer Electronics Control) that is embedded within the HDMI signal.

### Low-Profile Installation

The DGE-100 mounts conveniently to a wall, ceiling, or other flat surface. Its compact, surface-mountable form factor fits easily behind a flat panel display, beneath a tabletop, or inside a lectern or other furniture. It can even be attached directly to a single rack rail in the back of an equipment cabinet. The DGE-100 can be powered using the included wall mount power pack or via PoE (Power over Ethernet) for a true single-wire solution.

### Enterprise-Grade Security

The DGE-100 employs enterprise-grade networking with robust security features such as 802.1X authentication, TLS encryption, HTTPS connectivity, and Active Directory® service integration. These features help to protect your network and to ensure compliance with your organization's network policies. Cloud-based provisioning and management streamlines the process of configuring, monitoring, and updating each DGE-100 on the network. Additional support for SNMP allows the DGE-100 to be monitored by your IT administrator.

### XiO Cloud Service

The DGE-100 is compatible with the XiO Cloud® service, which is an IoT (Internet of Things) based platform for remotely provisioning, monitoring, and managing Crestron devices across an enterprise or an entire client base. Built on the Microsoft® Azure® software platform and utilizing Microsoft's industry-leading Azure IoT Hub technology, XiO Cloud enables installers and IT managers to deploy and manage thousands of devices simultaneously. Unlike other virtual machine-based cloud solutions, Azure services provide unlimited scalability to suit the ever-growing needs of an enterprise. For more information, visit [www.crestron.com/xiocloud](http://www.crestron.com/xiocloud).

## Specifications

### Graphics Engine

Smart Graphics® technology, landscape or portrait orientation, local and remote annotation, multilanguage web browser<sup>3</sup>, multilanguage on-screen keyboard, screensaver, scalable dual streaming video windowing, displays any combination of HDMI® and streaming sources<sup>1,2</sup>, setup and diagnostics via web browser, on-screen UI, or cloud

### Languages

<b>Smart Graphics Technology</b>	Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Danish, Dutch, English (UK), English (US), Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Portuguese (Brazilian), Romanian, Russian, Slovak, Spanish, Swedish, Thai
<b>On-screen Keyboard</b>	Arabic, Chinese (Simplified), Croatian, Czech, Danish, Dutch, English (UK), English (US), Finnish, French (Canada), French (Switzerland), German, Hebrew, Hungarian, Italian, Japanese, Norwegian Bokmal, Polish, Portuguese, Russian, Serbian, Spanish, Swedish, Turkish

# DGE-100

## Digital Graphics Engine 100

<b>Web Browser</b>	Arabic, Bulgarian, Catalan, Chinese, Croatian, Czech, Danish, Dutch, English, Filipino, Finnish, French, German, Greek, Hebrew, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Latvian, Lithuanian, Norwegian Bokmal, Pashto, Persian, Polish, Portuguese, Romanian, Romansh, Russian, Serbian, Slovak, Slovenian, Spanish, Swedish, Thai, Turkish, Ukrainian, Vietnamese
--------------------	---

### Memory

<b>RAM</b>	2 GB DDR3-SDRAM
<b>Flash</b>	4 GB
<b>Maximum Project Size</b>	1 GB

### Communications

<b>Ethernet</b>	100 Mbps, autoswitching, autonegotiating, autodiscovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SNMP, IPv4 or IPv6, Active Directory® authentication, HTTPS web browser setup, XiO Cloud® client, IEEE 802.1X, IEEE 802.3af and IEEE 802.3at Type 1 compliant, Crestron control system integration
<b>USB Host</b>	Supports TSD-2220 touch screen display and most third-party USB HID compliant peripherals
<b>USB Device</b>	For computer console (installer setup and firmware updates)
<b>RS-232</b>	2-way device control and monitoring up to 115.2k baud with hardware and software handshaking (via control system)
<b>IR/Serial</b>	1-way device control via infrared up to 1.1 MHz or serial TTL/RS-232 (0–5V) up to 19200 baud (via control system)
<b>HDMI</b>	HDCP 1.4, EDID, CEC

### Pointing Device Support

Compatible with the TSD-2220 touch screen display and most third-party USB HID compliant touch screens, mice, and keyboards

### Streaming Decoder

<b>Video Formats</b>	H.264 (MPEG-4 part 10 AVC), MJPEG
<b>Audio Formats</b>	AAC stereo
<b>Bitrates</b>	Up to 25 Mbps <sup>1</sup>

<b>Resolutions</b>	Up to 1080p60
--------------------	---------------

### Video

<b>Input Signal Types</b>	HDMI (DVI and dual-mode DisplayPort™ signal compatible <sup>4</sup> )
<b>Output Signal Types</b>	HDMI (DVI compatible <sup>4</sup> )
<b>Input Resolutions</b>	640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), plus any other resolution allowed by HDMI up to 148MHz pixel clock

**NOTE:** Interlaced video is not supported

<b>Output Resolutions</b>	640x480@60Hz, 800x600@60Hz, 1024x768@60Hz <sup>5</sup> , 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x800@60Hz <sup>5</sup> , 1366x768@60Hz <sup>5</sup> , 1440x900@60Hz <sup>5</sup> , 1600x900@60Hz <sup>6</sup> , 1600x1200@60Hz, 1680x1050@60Hz <sup>5</sup> , 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz
---------------------------	---

### Audio

<b>Input Signal Types</b>	HDMI (dual-mode DisplayPort compatible <sup>4</sup> )
<b>Output Signal Types</b>	HDMI
<b>Input/Output Formats</b>	2 channel LPCM
<b>Audio Feedback Formats</b>	MP3

### Connectors

<b>CONSOLE (USB)</b>	(1) USB Micro A connector, female; USB computer console port; Type A to Micro A USB cable included
----------------------	--

# DGE-100

## Digital Graphics Engine 100

<b>IR 1-2</b>	(1) 4-pin 3.5 mm detachable terminal block; Comprises (2) IR/serial ports; IR output to 1.1 MHz; 1-way serial TTL/RS-232 (0-5V) up to 19200 baud
<b>COM</b>	(1) 5-pin 3.5 mm detachable terminal block; Bidirectional RS-232 port; Up to 115.2k baud, hardware and software handshaking support
<b>HDMI INPUT</b>	(1) HDMI Type A connector, female; HDMI digital video/audio input; DVI and dual-mode DisplayPort signal compatible <sup>4</sup>
<b>HDMI OUTPUT</b>	(1) HDMI Type A connector, female; HDMI digital video/audio output; DVI compatible <sup>4</sup>
<b>USB</b>	(1) USB Type A connector, female; USB 2.0 host port for connecting a USB HID compliant touch screen, mouse, or keyboard
<b>LAN PoE</b>	(1) 8-pin RJ-45 connector, female; 100BASE-TX Ethernet port; Power over Ethernet (PoE) compliant
<b>24VDC 0.75A</b>	(1) 2.1 x 5.5 mm DC power connector; 24VDC power input; PW-2407WU power pack included
<b>G</b>	(1) 6-32 screw; Chassis ground lug

### Controls and Indicators

<b>PWR</b>	(1) Green LED, indicates operating power is present via the local power pack or PoE (Power over Ethernet); Flashes while the device is booting
<b>RESET</b>	(1) Recessed push button for hardware reset
<b>SETUP</b>	(1) Red LED and (1) recessed push button for Ethernet setup
<b>ONLINE</b>	(1) Green LED, indicates a connection is established to a control system via Ethernet
<b>HDMI IN/OUT</b>	(2) Green LEDs, indicate the presence of an HDMI signal at the HDMI input or output, respectively
<b>LAN PoE</b>	(1) Green LED and (1) amber LED; Green LED indicates the Ethernet link status; Amber LED indicates Ethernet activity

### Power

<b>PoE (Power over Ethernet)</b>	IEEE 802.3at Type 1 (802.3af compatible) Class 0 (12.95 W) PoE Powered Device
<b>Power Pack (Included)</b>	Input: 100-240VAC, 50/60 Hz; Output: 0.75A @ 24VDC; Model: PW-2407WU
<b>Power Consumption</b>	8 W (typical)

### Environmental

<b>Temperature</b>	32° to 104°F (0° to 40°C)
<b>Humidity</b>	10% to 90% RH (noncondensing)
<b>Heat Dissipation</b>	27.3 BTU/hr

### Enclosure

<b>Chassis</b>	Metal, black finish, (2) integral mounting flanges, vented sides
<b>Mounting</b>	Freestanding, surface mount, or attach to a single rack rail

### Dimensions

<b>Height</b>	6.42 in. (163 mm)
<b>Width</b>	7.40 in. (188 mm)
<b>Depth</b>	1.35 in. (35 mm)

### Weight

19.6 oz (554 g)

### Compliance

**Regulatory Model: DGE-100;**  
IC, CE, FCC Part 15 Class B digital device  
To search for product certificates, refer to [support.crestron.com/app/certificates](http://support.crestron.com/app/certificates).

### Model

**DGE-100**  
Digital Graphics Engine 100

### Included Accessories

**PW-2407WU**  
Wall Mount Power Pack, 24VDC, 0.75A, 2.1 mm, Universal

### Available Accessories

For a list of available accessories, visit the [DGE-100](#) product page.

# DGE-100

## Digital Graphics Engine 100

### Notes:

1. The DGE-100 supports up to two simultaneous streaming inputs with a maximum combined total bitrate of 25 Mbps.
2. The HDMI® input signal cannot be downscaled more than 4 times. For instance, a 1920x1080 source signal can be displayed no smaller than 480x270 pixels.
3. Web browsing, weather information, and certain other functions require an internet connection.
4. HDMI connections require an appropriate adapter or interface cable to accommodate a DVI or Dual-Mode DisplayPort™ signal. [CBL-HD-DVI](#) interface cables are available separately.
5. The output resolution is with or without reduced blanking.
6. The output resolution is with reduced blanking only.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or contact us for additional information by visiting [www.crestron.com/contact/our-locations](http://www.crestron.com/contact/our-locations) for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

The product warranty can be found at [www.crestron.com/warranty](http://www.crestron.com/warranty).

The specific patents that cover Crestron products are listed online at [www.crestron.com/legal/patents](http://www.crestron.com/legal/patents).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, AirMedia, DigitalMedia, Smart Graphics, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Active Directory, Azure, and Microsoft are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. DisplayPort is either a trademark or a registered trademark of Video Electronics Standards Association in the United States and/or other countries. Wi-Fi is either a trademark or a registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

## HDMI

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 10/27/22

# DGE-100

## Digital Graphics Engine 100

