

Crestron		NVS-200	
Description		Network Video Streamer	
Number of documented streams:	4	Documented Simultaneous Streams:	10

TSX

MJPEG

Supported:	Yes		
Resolution:	D1 (720x480/720x576)	Camera Quality Setting:	Good
Frames per second (fps):	30	Switching Time:	1~2 seconds
URL with user name and password:			
http://<username>:<password>@<IP Address>/video.mjpg			
URL without username and password			
http://<IP Address>/video.mjpg			
URL Example			
http://admin:admin@172.30.152.76/video.mjpg			

H.264

Supported	Yes		
Resolution:	D1 (720x480/720x576)	Max Bandwidth	2 Mb/s
Frames per second (fps):	30	Switching Time	
I-Frame Setting	1/S		
URL with user name password:			
rtsp://<username>:<password>@<IP address>/live.sdp			
URL without user name password:			
rtsp://<IP address>/live.sdp			
URL Multicast:			
-			
URL Example			
http://admin:admin@172.30.152.76/live2.sdp			

TPMC-V12/15, DGE-2. TPMC-8X-GA**MJPEG**

Supported:	Yes		
Resolution:	704x480	Camera Quality Setting:	4CIF. Standard
Frames per second (fps):	10fps	Switching Time:	2-4 sec
URL with user name and password:			
http://<ipaddress>/video2.mjpg?user=<username>&pw=<password>			
URL without username and password			
N/A			
URL Example			
http://172.30.185.125/video2.mjpg?user=admin&pw=admin			

H.264

Supported	Yes		
Resolution:	704x480	Max Bandwidth	512Kbps
Frames per second (fps):	10fps 4CIF. Standard	Switching Time	
I-Frame Setting	1 sec		
URL with user name password:			
http://<ipaddress>/video2.mjpg?user=<username>&pw=<password>			
URL without user name password:			
rtsp://<ipaddress>/live.sdp			
URL Multicast:			
-			
URL Example			
http://172.30.185.125/video2.mjpg?user=admin&pw=admin			

TPMC-4SM**MJPEG**

Supported:	Yes		
Resolution:	QCIF (176x144)	Camera Quality Setting:	Good
Frames per second (fps):	10	Switching Time:	3~8 seconds
URL with user name and password:			
http://<IP Address>/video.mjpg?user=<username>&pw=<password>			
URL without username and password			
http://<IP Address>/video.mjpg			
URL Example			
http://172.30.152.76/video.mjpg?user=admin&pw=admin			

H.264

Supported	Yes		
Resolution:	QCIF (176x144)	Max Bandwidth	512 Kbps
Frames per second (fps):	10	Switching Time	
I-Frame Setting	1/S		
URL with user name password:			
rtsp://<username>:<password>@<IP address>/live.sdp			
URL without user name password:			
rtsp://<IP address>/live.sdp			
URL Multicast:			
N/A			
URL Example			
http://admin:admin@172.30.152.76/live2.sdp			

Crestron App**MJPEG**

Supported:	Yes		
Resolution:	704x480	Camera Quality Setting:	4CIF. Standard
Frames per second (fps):	10	Switching Time:	2-4 sec
URL with user name and password:			
http://<Ipaddress>/video2.mjpg?user=<username>&pw=<password>			
URL without username and password			
N/A			
URL Example			
http://172.30.185.125/video2.mjpg?user=admin&pw=admin			

H.264

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
N/A			
URL Multicast:			
N/A			
URL Example			
N/A			