

Zūm™ Light Control System, Floor Hub



- *Centralized management and time clock for Zūm™ wireless commercial lighting systems*
- *Web-based user interface for easy configuration, control, scheduling, and monitoring*
- *Time clock for automation of room lighting and sensing behavior*
- *Supports 30 Zūm Net Wireless Gateways*
- *Control up to 1,000 rooms*
- *BACnet support, control up to 1,980 BACnet objects*
- *Dedicated Control Subnet*
- *Gigabit Ethernet networking*
- *Enterprise-grade security*
- *Enables integration with non-Zūm Crestron lighting systems, control systems, touch screens, shading, HVAC, and more*
- *Single-space rack-mountable*
- *Universal 100–240 V external power supply*
- *Meets UL® 916 standards for energy management equipment*
- *Meets CEC Title 24, ASHRAE® 90.1, and IECC® standards when properly configured³*

The Crestron® Zūm™ Floor Hub ([ZUM-FLOOR-HUB](#)) enables web-based management and control of rooms equipped with Zūm light control systems. The Zūm™ Floor Hub is capable of controlling up to 1,000 rooms. The Zūm™ Floor Hub can also manage external rooms that are controlled by non-Zūm equipment such as a GLPP, GLPAC-DIMFLV, or DIN-AP3 series system.

Zūm Net Wireless Communication

Connect up to 30 Zūm Net Wireless Gateways ([ZUMNET-GATEWAY](#)) to enable communication between the Zūm™ Floor Hub and the Zūm room. The ZUMNET-GATEWAY communicates with the Zūm room using Zūm Net Wireless technology and relays communications via Ethernet to the Zūm Floor Hub. One Zūm Network Bridge ([ZUMMESH-NETBRIDGE¹](#)) is required in each Zūm room. Up to 50 Zūm Network Bridges can be paired with a ZUMNET-GATEWAY.

Web-Based Management

A simple web browser user interface provides everything needed to manage, monitor, and schedule all of the available Zūm rooms on the network. Using a laptop computer, the wireless gateways and network bridges are quickly found, named, and configured to work with the Zūm Floor Hub, allowing the status of each room's lighting system to be viewed and controlled. User-friendly icons display the status of the

devices in each room, indicating active lighting scenes, individual lighting loads, daylight levels, occupancy detection, and scheduled time clock events. Any errors are also displayed to facilitate troubleshooting.

Time Clock

A built-in time clock enables lighting control to be automated based on the time of day. A group of similar rooms can be assigned a Room Category (such as Office, Conference Room, or Hallway) to allow consistent control and programming across all of the rooms.

The time clock allows Day Patterns to be arranged for each Room Category, with up to 24 Room States scheduled over a 24 hour period. Different Day Patterns can be defined for weekdays, weekends, half-days, holidays, etc., and then assigned to the calendar. To get going quickly, the calendar comes pre-populated with typical day patterns and a selection of U.S. holidays in place.

BACnet™ Communications Protocol

Communicate with a Building Management System (BMS) to provide control of HVAC, fire/life safety, lighting, and other building automation systems. The ZUM-FLOOR-HUB supports up to 1,980 BACnet objects.

Non-Zūm System Integration

In addition to managing rooms equipped with Zūm lighting control, the Zūm Floor Hub also enables integration with other Crestron systems over an Ethernet connection. Two methods of integration are available as follows:

- **External Rooms:** Any room that uses a Crestron lighting control system other than the Zūm Floor Hub, such as a GLPP, GLPAC-DIMFLV, or DIN-AP3. The room can be added to the Zūm network as a virtual room allowing it to be monitored, controlled, and scheduled alongside Zūm rooms ^{2,3}
- **Mirrored Rooms:** Any Zūm room equipped with a Zūm system that is configured to be monitored and controlled by an external Crestron control system. This allows for enhanced control of the room using a Crestron touch screen or handheld remote, as well as integration with shading, climate control, AV, and other equipment ^{2,3}

Zūm™ Light Control System, Floor Hub

Specifications

Device Support and Time Clock

Wireless Gateways	30 maximum
Network Bridges and External Rooms	1,000 maximum combined
External Rooms and Mirrored Rooms	Varies by control system based on hardware capabilities and program complexity ² ;
Room Categories	100 maximum
Room States	20 maximum
Room States in a Day Pattern	24 maximum per Room Category

Communications

Ethernet	10/100/1000 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, industry-standard TCP/IP stack, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), FIPS 140-2 compliant encryption, IEEE 802.1X, SNMP, IPv4 or IPv6, Active Directory® authentication, IIS v.6.0 web server
Control Subnet	10/100/1000 Mbps Ethernet, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP server, DNS Server, port forwarding, isolation mode
USB	Supports computer console via front panel USB 2.0 device port

Connectors and Card Slots

MEMORY	(1) SD memory card slot; Accepts one 32 GB SD or SDHC card to enable logging and for troubleshooting purposes
USB	(1) USB Type A connector, female; USB 2.0 host port (not used)
LAN	(1) 8-pin RJ-45 connector, female; 10Base-T/100Base-TX/1000Base-T Ethernet port; Connects to the customer's LAN
CONTROL SUBNET	(1) 8-pin RJ-45 connector, female; 10Base-T/100Base-TX/1000Base-T Ethernet port; Provides a dedicated local network for Zūm Net wireless gateways

NET	(1) 4-pin 3.5 mm detachable terminal block; Not used
24VDC 2.0A	(1) 2.1 x 5.5 mm DC power connector; 24 VDC power input; Passes through to NET port; PW-2420RU power pack included
G	(1) 6-32 screw; Chassis ground lug

Controls and Indicators

PWR	(1) Green LED; Indicates operating power supplied from the included power pack
NET	(1) Amber LED; Not used
MSG	(1) Red LED; Indicates that the Zūm Floor Hub has generated an error message
HW-R	(1) Recessed pushbutton for hardware reset
SW-R	(1) Recessed pushbutton for software reset
LAN (rear)	(2) Bi-color green/amber LEDs; Left LED indicates Ethernet link status and connection speed; Right LED indicates Ethernet activity
CONTROL SUBNET (rear)	(2) Bi-color green/amber LEDs; Left LED indicates Ethernet link status and connection speed; Right LED indicates Ethernet activity

Power

Power Pack	Input: 100–240 VAC, 50/60 Hz Output: 2.5 A @ 24 VDC Model: PW-2420RU
Power Consumption	15 W

Zūm™ Light Control System, Floor Hub

Environmental

Temperature	41° to 113°F (5° to 45°C)
Humidity	10% to 90% RH (noncondensing)
Heat Dissipation	50 BTU/hr

Construction

Chassis	Metal, black finish
Faceplate	Extruded metal, black finish, polycarbonate label overlay
Mounting	Freestanding or 1 RU 19-in. rack-mountable; Adhesive feet and rack ears included

Dimensions

Height	1.70 in. (44 mm) without feet
Width	17.32 in. (440 mm); 19.00 in. (483 mm) with rack ears
Depth	6.56 in. (167 mm)

Weight

3.1 lb (1.42 kg)

Compliance

UL Listed for US & Canada, IC, CE, FCC Part 15 Class B digital device, UL 916

Models

ZUM-FLOOR-HUB

ZUM-FLOOR-HUB-LIGHT

Included Accessories

PW-2420RU

Available Accessories

ZUMMESH-NETBRIDGE

Zūm™ Network Bridge

ZUMNET-GATEWAY

Zūm™ Net Wireless Gateway

Notes:

1. Item(s) sold separately. Refer to each product's spec sheet for more information.
2. SIMPL+ software modules are provided for use in commissioning a Crestron control system to work with the Zūm Floor Hub. The software modules run within the control system program and provide virtual connections for all the necessary intersystem control signals. A separate dedicated module is required for each external room and each mirrored room. Control systems are limited in the number of modules supported, ranging from 0 to 200 depending on the model. For further assistance, please contact Crestron Commercial Lighting Support via email at clclighting@crestron.com or by calling 855-644-7643.
3. Each non-Zūm system must be custom commissioned to provide the appropriate control logic required to communicate and operate as part of the Zūm network. Once integrated, each "external room" effectively becomes a part of the Zūm ecosystem.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <https://www.crestron.com/How-To-Buy/Find-a-Representative> or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty for 3 years, except for the touch screen display which is covered for 90 days. Refer to <https://www.crestron.com/warranty> for full details

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Zūm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. BACnet and ASHRAE are either a trademarks or registered trademarks of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. in the United States and/or other countries. ICC is either a trademark or registered trademark of International Code Council, Inc. in the United States and/or other countries. Active Directory is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. UL is either a trademark or registered trademark of UL LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2019 Crestron Electronics, Inc.

Rev 08/16/19

Zūm™ Light Control System, Floor Hub

