



**NOTES:**

- 1 "CRESTRON" CABLE:  
(1) PAIR #18AWG,  
(1) TWISTED PAIR 22AWG  
W/SHIELD (BY E.C.)  
NON-PLENUM PN: CRESTRON-NP-TL  
PLENUM PN: CRESTRON-P-TL
- 2 RS-232 CABLE:  
(1) TWISTED PAIR 22AWG  
(1) SHIELD  
DB-9 CONNECTOR  
(BY E.C.)
- 3 CABLE:  
(1) TWISTED PAIR 18AWG  
(1) SHIELD  
(BY E.C.)
- 4 CABLE:  
CAT5E ETHERNET

\*\*\*ALL PHYSICAL DEVICE LOCATIONS TO BE COORDINATED WITH ARCHITECT.

CRESTRON WIRING RUNS SHOWN AS HOME RUN TO EACH DEVICE FOR OPTIMAL PERFORMANCE. DAISY CHAIN AND OR STAR TOPOLOGIES ARE PERMITTED TO SUIT INSTALLATION NEEDS. TOTAL END TO END WIRE LENGTH NOT TO EXCEED 500'.

REVISIONS	DATE	BY
00	12-03-08	VB

PROJECT:	120V 24-CKT SWITCHING SYSTEM
LOCATION:	
QUOTE #:	
SALES REP:	
DISTRIBUTOR:	
	PO #:

15 Volvo Drive  
Rockleigh NJ 07647  
Tel: 888-273-7876  
Fax: 201-767-6011  
www.crestron.com

TITLE:  
ONE-LINE  
RISER  
(FOR INFORMATION  
ONLY)

DRAWING:  
1.0