

Zūm® Wired J-Box Power Supply



- *Zūm® wired junction box mounted power supply*
- *Powers Zūm keypads, presence detectors, and daylight sensors (sold separately)*
- Flying lead wiring connections
- Knockout mount to a standard 4 in. square junction box

The Zūm® Wired ZUMLINK-JBOX-PSU delivers additional Zūm Link power to the in-room system. Equipped with four Zūm Link connections, it provides power and communication distribution to Zūm Link devices via plug-and-play wiring.

Zūm Link Wired Technology

Zūm Link technology enables in-room lighting control through keypads and sensors wired to controllers. Zūm Wired devices connect via CBL-CAT5E-ZUMLINK-P CAT5e cable (sold separately) to RJ-45 ports to provide simple daisy-chaining and lighting control of compatible loads. The Zūm Wired devices work together in a local ecosystem to provide customized solutions using the Zūm app via Bluetooth connectivity.

Easy Installation

For flexibility and ease-of-use, install Zūm devices (load controllers, keypads, and presence detectors) and connect them with Zūm Link (CBL-CAT5E-ZUMLINK-P) or Zūm Net (CBL-CAT5E-ZUMNET-P) CAT5e cable. Nonsystem presence detectors may also be installed to any load controller with analog inputs.

Specifications**Power Requirements**

AC Input Power	100-277VAC, 50/60 Hz
Zūm Link Output Current	250mA per segment; 500mA total across both segments (4 ports); Segment 1: ports 1 and 2 Segment 2: ports 3 and 4
Zūm Link Pass-through Current	250mA max; Including internal power supply: 750mA cumulative maximum

Wired Communications

ZUMLINK	(4) RJ-45 ports
---------	-----------------

Controls and Indicators

PWR Status	(1) green LED; Power indicator
------------	-----------------------------------

Connections

Hot	(1) 14 AWG Class 1 flying lead; Black, line power input
Neutral	(1) 14 AWG Class 1 flying lead; White, neutral

Environmental

Rating	IP20
Temperature	32° to 104°F (0° to 40°C)

Construction

Housing	Plastic, white, UL 94 5VA flame rated
Mounting	Mounts to the side of a 4 in. square junction box via a 1/2 in. conduit knockout; Meets the requirements of UL 2043 for installation in an environmental air-handling (plenum) space

Dimensions

Height	4.93 in. (125 mm)
Width	4.25 in. (108 mm)
Depth	2.03 in. (52 mm)

Weight

7 oz (199 g)

Compliance

Regulatory Model: M202107003

Zūm® Wired J-Box Power Supply

cUL916, cUL2043

UL® Listed for US & Canada, IC, FCC Part 15 Class A digital device, UL 916, UL 2043, UL 94 5VA

Model

ZUMLINK-JBOX-PSU

Zūm® Wired J-Box Power Supply

Available Accessories

For a list of available accessories, visit the [ZUMLINK-JBOX-PSU](#) product page.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

The product warranty can be found at www.crestron.com/warranty.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Zūm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of UL LLC in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2023 Crestron Electronics, Inc.

Rev 10/17/23

Zūm® Wired J-Box Power Supply

