

# TST-600-DS

## Table Dock for TST-600 & TST-602

The TST-600-DS is the table dock that is included as standard with the [TST-600](#) and [TST-602](#) Wireless Touch Screens. It provides a convenient solution for charging the touch screen's internal battery. It is also available separately as an add-on accessory for the [TST-600-WALL](#) and [TST-602-WALL](#) Wall Mount Wireless Touch Screens to provide an alternate tabletop charging option.

The TST-600-DS features a low-profile design, allowing it to fit easily in a cabinet or drawer, or on a countertop or side table. Its angled cradle facilitates full use of the touch screen while charging. It can also provide a wired Ethernet connection for the touch screen while docked.

For easy, versatile placement, the table dock features a single flexible hookup cable. The 9 ft (2.75 m) cable extends from the rear of the table dock to a compact interface module ([TST-600-IMCW](#), included), which may be installed in a wall-mounted electrical box, or attached to any flat surface or a single rack rail. The interface module provides wired connections for power and Ethernet.<sup>[1]</sup>

The optional swivel mount kit ([TST-600-SMK](#), sold separately) allows the table dock to be affixed to the tabletop, with the ability to rotate it up to 330 degrees.

### SPECIFICATIONS

Note: See also [TST-600-IMCW](#) for additional specifications.

#### Connectors

Integral 9 ft (2.75 m) cable with 10-pin RJ50 male connector;  
Connects to [TST-600-IMCW](#) interface module (included)

#### Power Requirements

The TST-600-DS table dock is a passive device requiring no power; a [TST-600-IMCW](#) interface module and power pack are included to provide power and other connectivity for the TST-600 or TST-602 touch screen; refer to [TST-600](#), [TST-602](#), and [TST-600-IMCW](#) specifications for additional power requirements

#### Environmental

Temperature: 32° to 112°F (0° to 45°C);  
50° to 104°F (10° to 40°C) while charging

Humidity: 10% to 90% RH (non-condensing)

#### Enclosure

Plastic, angled cradle, integral cable assembly



#### Dimensions

Height: 1.82 in (47 mm)

Width: 4.90 in (125 mm)

Depth: 5.84 in (149 mm)

Note: Combined height of the TST-600-DS table dock with TST-600 or TST-602 touch screen docked is 3.30 in (84 mm).

#### Weight

7.8 oz (222 g)

### MODELS & ACCESSORIES

#### Available Models

[TST-600-DS-B-S](#): Table Dock for TST-600 & TST-602, Black Smooth

[TST-600-DS-B-T](#): Table Dock for TST-600 & TST-602, Black Textured

[TST-600-DS-W-S](#): Table Dock for TST-600 & TST-602, White Smooth

#### Included Accessories

[TST-600-IMCW](#): Interface Module (Qty. 1 included)

[PW-2407WU](#): Wall Mount Power Pack, (Qty. 1 included)

#### Available Accessories

[TST-600-SMK](#): Swivel Mount Kit

[CBL-CAT5E-P-50](#): Ethernet LAN Cable, Plenum, 50 ft

Notes:

1. See [TST-600-IMCW](#) specifications for additional information.

# TST-600-DS Table Dock for TST-600 & TST-602

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.

