

<b>Vivotek</b>		<b>FD8162 (1080)</b>	
Description		Network Bullet Camera	
Number of documented streams:	3	Documented Simultaneous Streams:	4

## TSX

### MJPEG

Supported:	Yes		
Resolution:	1008x768	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	1~2
URL with user name and password: http://<IP address>:<port>/video.mjpg?user=<username>&pw=<password> - video1.mjpg - 2,3,4, etc.			
URL without username and password N/A			
URL Example http://192.168.1.106:80/video.mjpg?user=admin&pw=admin			

### H.264

Supported	Yes		
Resolution:	1008x768	Max Bandwidth	2Mbps
Frames per second (fps):	15	Switching Time	1~2
I-Frame Setting	1/S		
URL with user name password: rtsp://<IP address>:<port>/live.sdp?user=<username>&pw=<password> - live.sdp - live1.sdp - 2,3,4, etc.			
URL without user name password: rtsp://<IP address>:<port>/live.sdp - live.sdp - live1.sdp - 2,3,4, etc.			
URL Multicast: http://192.168.1.106:80/live.sdp?user=admin&pw=admin			
URL Example rtsp://192.168.1.106:554/live.sdp?user=admin&pw=admin			

**TPMC-V12/15, DGE-2. TPMC-8X-GA****MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Good
Frames per second (fps):	15	Switching Time:	2-4 sec
URL with user name and password:			
http://<IP_address>:<port>/<[video1.mjpeg video2.mjpeg video3.mjpeg video4.mjpeg]>?user=admin&pw=admin			
URL without username and password			
N/A			
URL Example			
http://172.30.176.226:80/video.mjpg?user=admin&pw=admin			

**H.264**

Supported	Yes		
Resolution:	1280x720	Max Bandwidth	768Kbps
Frames per second (fps):	15	Switching Time	2-4 sec
I-Frame Setting	1/2S		
URL with user name password:			
rtsp://<IP address>:<port>/<[live.sdp live2.sdp live3.sdp live4.sdp]>			
URL without user name password:			
rtsp://<IP address>:554/live.sdp			
URL Multicast:			
Yes			
URL Example			
rtsp://172.30.176.226:554/live.sdp?user=admin&pw=admin			

**TPMC-4SM****MJPEG**

Supported:	Yes		
Resolution:	240x192	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	6~7 seconds
URL with user name and password: http://<IP address>:<port>/video.mjpg?user=<username>&pw=<password> - video1.mjpeg - 2,3,4, etc.			
URL without username and password N/A			
URL Example http://192.168.1.106:80/video.mjpg?user=admin&pw=admin			

**H.264**

Supported	Yes		
Resolution:	240x192	Max Bandwidth	256Kbps
Frames per second (fps):	15	Switching Time	6~7 seconds
I-Frame Setting	1/S		
URL with user name password: rtsp://<IP address>:<port>/live.sdp?user=<username>&pw=<password> - live.sdp - live1.sdp - 2,3,4, etc.			
URL without user name password: rtsp://<IP address>:<port>/live.sdp - live.sdp - live1.sdp - 2,3,4, etc.			
URL Multicast: N/A			
URL Example rtsp://192.168.1.106:554/live.sdp?user=admin&pw=admin			

**Crestron App****MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Standard
Frames per second (fps):	5	Switching Time:	2-4sec
URL with user name and password:			
http://<Ipaddress>:<Port>/video.mjpg?user=admin&pw=admin			
URL without username and password			
N/A			
URL Example			
http://172.30.177.85:80/video.mjpg?user=admin&pw=admin			

**H.264**

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			