# Cable Retractors for FlipTops™

- > Provides an ideal cable management solution for Crestron FlipTops™
- > Keeps interface cables at-the-ready
- > Eliminates hanging cable loops beneath the table
- > Easy-to-use simply pull the cable out of the FlipTop™ compartment then press the lever to retract the cable
- > Patent-pending mechanism prevents whipping of the cable while retracting
- > Models available to support HDMI®, VGA, stereo audio, USB, Ethernet, HDBaseT®, and DigitalMedia 8G+™
- > Vertical or horizontal mounting options accommodate most tabletop applications



Each Crestron Cable Retractor features a patent-pending mechanism that dampens the rate of retraction to prevent the cable from whipping as it's pulled back into the FlipTop storage compartment. The retraction speed is installer adjustable to ensure full and effortless retraction without excessive force.

Up to three, four, or six cable retractors can be installed depending on the FlipTop model (see specifications for quantity and compatibility). Spacer inserts are available to fill any unused positions.<sup>[1]</sup>

Cable retractors can be oriented in two possible positions. As standard, the retractors hang vertically from the bottom of the FlipTop box allowing them to be hidden in a pedestal leg or similar space directly beneath the FlipTop. Using the horizontal mounting option, the cable retractors can be attached to the underside of the tabletop. Both options eliminate any loose hanging cable loops below the table.

A 7 foot (2.1 meter) long tail is provided at the back-end of each cable retractor beneath the tabletop. This tail can be plugged into a wall plate or floor box, or connected to a DigitalMedia $^{\text{TM}}$  transmitter or similar interface device mounted under the table.

Five CBLR cable retractor models are currently offered. These include HDMI®, VGA, stereo audio, USB, and CAT5e. The CAT5e model can be used to provide an Ethernet LAN connection, and is also compatible with HDBaseT® and DigitalMedia  $8G+^{TM}$  digital AV interfaces.



### **SPECIFICATIONS**

### FlipTop™ Compatibility

FlipTop Models	Cable Retractors Max. Quantity <sup>[1]</sup>	Required "FT" Bracket <sup>[2]</sup>	Horizontal "H" Bracket Option <sup>[2]</sup>
C2N-FTB-D FT-PWR-D QM-FTCC QM-FTCC-NB QM-FTDC QM-FTDC-NB QM-FTMC QM-FTMC-NB QM-FTMCSC QM-FTMCSC-NB	3	CBLRA-BRKT-3-FT	CBLRA-BRKT-3-H
C2N-FT-TPS4 C2N-FT-TPS4-U FT-PWR-D-LG QM-FTCC-TPS4	4	CBLRA-BRKT-4-FT	CBLRA-BRKT-4-H
FTI-PWR-D QMI-FTCC QMI-FTDC QMI-FTMC QMI-FTMCSC	4	CBLRAI-BRKT-4-FT	CBLRA-BRKT-4-H
FT-600 FT-TS600	3 (one side only)	Not Required	CBLRA-BRKT-3-H
FT-600 FT-TS600	6	Not Required	CBLRA-BRKT-3-H Qty. 2 Required
IM-FTCC-M IM-FTCCV-M IMI-FTCC-M IMI-FTCCV-M QMI-FTCC-TPS4	0 (not supported)	N/A	N/A

# Cable Retractors for FlipTops<sup>™</sup>



FlipTop FT-TS600 - Shown with 6 CBLR Cable Retractors installed



**HDMI®:** HDMI Type A, male-male, 3 ft (0.9 m) pull-out, 7 ft (2.1 m)

back-end tail

VGA: HD15, male-male, 3 ft (0.9 m) pull-out, 7 ft (2.1 m) back-end tail Audio: 3.5mm TRS mini phone plug, male-male, 3 ft (0.9 m) pull-out,

7 ft (2.1 m) back-end tail

USB: USB Type A, male-male, 3 ft (0.9 m) pull-out, 7 ft (2.1 m) back-end

CAT5E: T-568B straight-through RJ45, male-male, 3 ft (0.9 m) pull-out, 7 ft (2.1 m) back-end tail

**Environmental** 

Temperature: 41° to 104°F (5° to 40°C) Humidity: 10% to 90% RH (non-condensing)

**Enclosure** 

Metal, black

**Dimensions** 

Height: 22.69 in (577 mm) Width: 1.12 in (29 mm) Depth: 4.02 in (103 mm)

Mounted vertically using CBLRA-BRKT-3-FT, including FlipTop Box with lid closed and all required mounting brackets:

Height: 23.14 in (588 mm) Width: 6.75 in (172 mm) Depth: 7.74 in (197 mm)

Mounted horizontally using CBLRA-BRKT-3-FT and CBLRA-BRKT-3-H, including FlipTop Box with lid closed and all required mounting brackets:

Height: 9.44 in (240 mm) Width: 6.75 in (172 mm) **Depth:** 21.61 in (549 mm)



FlipTop C2N-FT-TPS4 – Shown with 4 CBLR Cable Retractors installed

Mounted vertically using CBLRA-BRKT-4-FT, including FlipTop Box with lid closed and all required mounting brackets:

**Height:** 23.46 in (596 mm) Width: 7.67 in (195 mm) Depth: 8.40 in (214 mm)

Mounted horizontally using CBLRA-BRKT-4-FT and CBLRA-BRKT-4-H, including FlipTop Box with lid closed and all required mounting brackets:

**Height:** 9.77 in (249 mm) Width: 8.50 in (216 mm) Depth: 22.18 in (564 mm)

Mounted vertically using CBLRAI-BRKT-4-FT, including FlipTop Box with lid closed and all required mounting brackets:

Height: 23.28 in (592 mm) Width: 7.67 in (195 mm) Depth: 8.34 in (212 mm)

Mounted horizontally using CBLRAI-BRKT-4-FT and CBLRA-BRKT-4-H, including FlipTop Box with lid closed and all required mounting brackets:

**Height:** 9.59 in (244 mm) Width: 7.67 in (195 mm) Depth: 22.25 in (565 mm)

Mounted vertically to both sides of a FT-600 or FT-TS600, including FlipTop Box with lid closed and all required mounting brackets:

Height: 23.43 in (595 mm) Width: 10.16 in (258 mm) Depth: 6.77 in (172 mm)

Mounted horizontally to both sides of a FT-600 or FT-TS600, using CBLRA-BRKT-3-H, including FlipTop Box with lid closed and all required mounting brackets:

**Height:** 9.65 in (245 mm) Width: 39.17 in (995 mm) **Depth:** 6.77 in (172 mm)



# Cable Retractors for FlipTops™

#### Weight

2.0 lb (908 g) each

#### **MODELS & ACCESSORIES**

#### **Available Models**

CBLR-HD: Cable Retractor for FlipTops™, HDMI® CBLR-VGA: Cable Retractor for FlipTops™, VGA CBLR-AUDIO: Cable Retractor for FlipTops™, Audio CBLR-USB: Cable Retractor for FlipTops™, USB CBLR-CAT5E: Cable Retractor for FlipTops<sup>™</sup>, CAT5e

### **Available Accessories**

CBLRA-BRKT-3-FT: Cable Retractor Mounting Bracket for Small FlipTops™ CBLRA-BRKT-4-FT: Cable Retractor Mounting Bracket for Large FlipTops™ CBLRAI-BRKT-4-FT: Cable Retractor Mounting Bracket for International FlipTops™

CBLRA-BRKT-3-H: Horizontal Mounting Option for up to 3 CBLR Cable Retractors

CBLRA-BRKT-4-H: Horizontal Mounting Option for up to 4 CBLR Cable Retractors

CBLRA-INSERT-BLANK: Blank Spacer Insert for Cable Retractor

Mounting Brackets CBLRA-INSERT-2WIRE: 2-Wire Spacer Insert for Cable Retractor

Mounting Brackets

FTA-CBLRA-INSERT-2WIRE-102: Cable Retractor Spacer Insert for

FlipTop™ 600 Series

#### Notes:

- 1. When installing fewer than the maximum quantity of cable retractors, a spacer insert is required to fill each unused cable retractor space. For FlipTop 600 Series, use the FTA-CBLRA-INSERT-2WIRE-102. For all other FlipTops, use the CBLRA-INSERT-2WIRE or CBLRA-INSERT-BLANK. All spacer inserts are sold separately.
- 2. Item sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G+, FlipTop, FlipTops, and QuickMedia

Alliance in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.



FT-TS600 with CBLR Cable Retractors in Vertical Orientation Retractors in Vertical Orientation



C2N-FT-TPS4 with CBLR Cable



C2N-FT-TPS4 with CBLR Cable Retractors in Horizontal Orientation



FT-TS600 with CBLR Cable Retractors in Horizontal Orientation

## Cable Retractors for FlipTops™ **CBLR**







