

Vivotek		IP8362 (1080)	
Description		Network Bullet Camera	
Number of documented streams:	4	Documented Simultaneous Streams:	4

TSX

MJPEG

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	1~2
URL with user name and password: http://<IP address>:<port>/video.mjpg?user=<username>&pw=<password> - video1.mjpg - 2,3,4, etc.			
URL without username and password N/A			
URL Example http://192.168.1.112:80/video.mjpg?user=admin&pw=admin			

H.264

Supported	Yes		
Resolution:	384x216	Max Bandwidth	2 Mb/s
Frames per second (fps):	15	Switching Time	1~2 seconds
I-Frame Setting	1/S		
URL with user name password: rtsp://<IP address>:<port>/live.sdp?user=<username>&pw=<password> - live.sdp - live1.sdp - 2,3,4, etc.			
URL without user name password: rtsp://<IP address>:<port>/live.sdp			
URL Multicast: -			
URL Example rtsp://192.168.1.112:554/live.sdp?user=admin&pw=admin			

TPMC-V12/15, DGE-2. TPMC-8X-GA**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Good
Frames per second (fps):	15	Switching Time:	1-2 secs
URL with user name and password:			
http://<username>.<password>@<IP_Address>:<Port>/<[video.mjpg video2.mjpg video3.mjpg video4.mjpg]>			
URL without username and password			
http://<Ipaddress>:80/video.mjpg			
URL Example			
http://admin.admin@172.30.176.154:80/video.mjpg			

H.264

Supported	Yes		
Resolution:	1280x720	Max Bandwidth	768Kbps
Frames per second (fps):	15	Switching Time	1-2 secs
I-Frame Setting	1S		
URL with user name password:			
rtsp://<IP address>:<port>/<[live1.sdp live2.sdp live3.sdp live4.sdp]>			
URL without user name password:			
rtsp://<IP Address>:554/live.sdp			
URL Multicast:			
Yes			
URL Example			
rtsp://admin.admin@172.30.176.32:554/live.sdp			

TPMC-4SM**MJPEG**

Supported:	Yes		
Resolution:	384x216	Camera Quality Setting:	good
Frames per second (fps):	15	Switching Time:	6~7
URL with user name and password: http://<IP address>:<port>/video.mjpg?user=<username>&pw=<password> - video1.mjpeg - 2,3,4, etc.			
URL without username and password -			
URL Example -			

H.264

Supported	Yes		
Resolution:	384x216	Max Bandwidth	128Kbps
Frames per second (fps):	15	Switching Time	3~7
I-Frame Setting	1/S		
URL with user name password: rtsp://<IP address>:<port>/live.sdp?user=<username>&pw=<password> - live.sdp - live1.sdp - 2,3,4, etc.			
URL without user name password: -			
URL Multicast: -			
URL Example -			

Crestron App**MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	Standard
Frames per second (fps):	5	Switching Time:	2-4sec
URL with user name and password:			
http://<Ipaddress>:<Port>/video.mjpg?user=admin&pw=admin			
URL without username and password			
N/A			
URL Example			
http://172.30.176.32:80/video.mjpg?user=admin&pw=admin			

H.264

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			