

ULTIMATE OD6T-PRIMED-EACH

Ultimate 6 in. 2-Way Outdoor Speaker, Ribbon Tweeter, Primed Paintable, Single

- Weatherproof 2-way outdoor speaker
- Co-located woofer and ribbon tweeter for phase coherence and wide dispersion resulting in a larger listening area
- Designed for landscape and wall mount applications
- 5.25 in. (133 mm) glass fiber woofer
- 3 in. (76 mm) planar magnetic ribbon tweeter
- IP65 rated for dust and water, weatherized construction
- 8 Ohms nominal impedance
- Built-in 70/100V transformer
- 75 W @ 70V, 150 W @ 100V program power handling
- 150 W (Program), and 300 W (Peak) power handling
- 120 Hz to 20 kHz (± 3 dB) frequency response
- 110° horizontal and 75° vertical coverage
- Primed finish paintable to blend with the surroundings

Crestron® Ultimate speakers made by Origin Acoustics deliver the pinnacle of performance for demanding outdoor installations. Select materials, top shelf components and a high-end appearance underscore the design behind each model. The result is a no-compromise outdoor speaker designed to be staked directly into the ground or mounted to an exterior wall, fence post, or tree.

The ULTIMATE OD6T-PRIMED-EACH 2-way weatherproof outdoor speaker features a 5.25 in. (133 mm) glass fiber woofer with a co-located 3 in. (76 mm) planar magnetic ribbon tweeter for crisp highs with consistent coverage across a wide listening area.

Each speaker includes a 24 in. (610 mm) direct-burial speaker wire that is permanently attached to the speaker and routed through the mounting base for a clean, reliable installation. A suitable electrical box (not included) is advised for termination of the speaker wiring. A pair of waterproof wire nuts are included to terminate the bare wire ends.

Use the ground stake ([SPKA-STAKE-OD-18](#)) to mount and install the speaker directly into the ground or use the tree or surface mount bracket ([SPKA-SMK/TREEMK-ULTIMATE-OD6](#)) to mount the speaker to an exterior wall, fence post, or tree.

NOTE: The ground stake and tree or surface mounted bracket are not included.

Specifications

Features & Performance

Woofer	5.25 in. (133 mm) glass fiber
Tweeter	3 in. (76 mm) planar magnetic ribbon
Crossover	Passive custom 12 dB/oct
Crossover Point	2 kHz
Impedance	8 Ohms nominal
Transformer Taps	75 W @ 70V; 150 W @ 100V
Frequency Response	120 Hz to 20 kHz (± 3 dB)
Frequency Range	95 Hz to 25 kHz (± 10 dB)
Power Handling (8 Ohms)	Program: 150 W; Peak: 300 W
Sensitivity	88 dB @ 1 W/1 M
Coverage	110° horizontal and 75° vertical coverage

Connections

Input	24 in. x 14 AWG (2.5 mm ²) pigtail with water proof wire nuts
Direct-burial Speaker Wire	24 in. (610 mm)

Environmental

Temperature	4° to 176°F (-15.5° to 80°C)
Humidity	10% to 90% RH (non-condensing)
Splash Resistance	IP65 rated for water

Construction

Enclosure	Color-molded composite
Baffle	UV treated HDPE
Grille	Electroplated and powder coated steel
Mounting	Ground stake, tree or surface mount

Dimensions

Height	9.25 in. (235 mm)
Width	6.65 in. (169 mm)
Depth	10.43 in. (265 mm)

ULTIMATE OD6T-PRIMED-EACH

Ultimate 6 in. 2-Way Outdoor Speaker, Ribbon Tweeter, Primed Paintable, Single

Weight

6.8 lb (3.1 kg)

Compliance

Regulatory Model: M202046011

CE, RoHS, FCC Part 15 Class B digital device

Models

ULTIMATE OD6T-PRIMED-EACH

Ultimate 6 in. 2-Way Outdoor Speaker, Ribbon Tweeter, Primed Paintable, Single

ULTIMATE OD6T-BRZ-T-EACH

Ultimate 6 in. 2-Way Outdoor Speaker, Ribbon Tweeter, Bronze Textured, Single

Available Accessories

For a list of available accessories, visit the [ULTIMATE OD6T-PRIMED-EACH](#) product page.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Origin Acoustics is either a trademark or a registered trademark of Origin Acoustics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2021 Crestron Electronics, Inc.

Rev 07/08/21

ULTIMATE OD6T-PRIMED-EACH

Ultimate 6 in. 2-Way Outdoor Speaker, Ribbon Tweeter, Primed Paintable, Single

