

DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable



- *Interoperability with a DM Lite® receiver or DMPS Lite™ switcher*
- *Point-to-point extension of an HDMI® signal over a CAT5e or higher cable*
- *DM Lite transmission distance up to 130 ft (40 m) for UHD and 4K signals or up to 230 ft (70 m) for 1080p, WUXGA, and 2K signals*
- *4K60 4:4:4 capability*
- *HDR10, HDR10+, and Dolby Vision® video formats*
- *Compliance with HDCP 2.3*
- *Automatic switching of HDMI inputs*
- *CEC (Consumer Electronics Control) pass-through capability*
- *EDID pass-through capability*
- *Compact, surface-mountable design*
- *Power from 24VDC power pack (included) or from remote DM Lite receiver or DMPS Lite switcher*

The HD-TX-4KZ-201 is a DM Lite® 4K60 4:4:4 transmitter designed to interoperate with a DM Lite® receiver or DMPS Lite™ switcher for the transmission of an HDMI® signal. A CAT5e or higher twisted pair cable is used to connect the HD-TX-4KZ-201 to the DM Lite receiver or DMPS Lite switcher. For 1080p, WUXGA, and 2K signals, a cable length of up to 230 ft (70 m) is supported. For UHD and 4K signals, a cable length of up to 130 ft (40 m) is supported.¹

Interoperability with a DM Lite Receiver or DMPS Lite Switcher

The DM Lite output port of the HD-TX-4KZ-201 must be connected to a DM Lite input port of a DM Lite receiver or DMPS Lite switcher. Examples of supported DM Lite 4K60 4:4:4 receivers are the HD-RX-4KZ-101, HD-RXA-4KZ-101, HD-RXC-4KZ-101, and HD-RXCA-4KZ-101. Supported DM Lite 4K60 4:2:0 receivers are the HD-RX-101-C-E, HD-RXC-101-C-E, HD-RX-201-C-E, HD-RX-101-C-1G-E, and HD-RXC-101-C-1G-E. Supported DMPS Lite switchers are the HD-PS622, HD-PS621, HD-PS402, HD-PS401, and HD-RX-4K-210-C-E(-POE).

The HD-TX-4KZ-201 can be configured and controlled only when it is used with a DMPS Lite switcher. The web interface of the switcher can be used to configure the HD-TX-4KZ-201. In addition, control system programming and .AV Framework™ software support of the HD-TX-4KZ-201 is hosted by the switcher.

4K60 4:4:4 and HDR Support

The HD-TX-4KZ-201 supports video resolutions up to 4K60 with 4:4:4 color sampling. HDR10, HDR10+, and Dolby Vision® video formats are also supported.²

Automatic Switching of Inputs

When the HD-TX-4KZ-201 is used with a DMPS Lite switcher, the web interface of the switcher or control system programming hosted by the switcher can be used to configure the switching behavior of the HD-TX-4KZ-201. Switching between the two HDMI inputs can occur based on the last connected input or on the routing priority assigned to each input. In addition, input selection push buttons on the front panel of the HD-TX-4KZ-201 enable the desired input to be selected manually.

Compact, Surface-Mountable Design

Compact in design, the HD-TX-4KZ-201 can be mounted onto a flat surface such as the underside of a table, behind a credenza, or inside a podium. It can also be attached to a single rack rail in the back of an equipment cabinet. The HD-TX-4KZ-201 can receive power from the included power pack or from the remote DM Lite receiver or DMPS Lite switcher.³

DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable

Specifications

Video

Input Signal Type	HDMI® with HDR10, HDR10+, Dolby Vision®, Deep Color, and 4K60 4:4:4 support ² (DVI and Dual-Mode DisplayPort™ interface compatible ⁴)
Output Signal Type	DM Lite® with HDR10, HDR10+, Dolby Vision, Deep Color, and 4K60 4:4:4 support ²
Copy Protection	HDCP 2.3
Resolutions	Common resolutions are listed in the following table.

Scan Type	Resolution	Frame Rate	Color Sampling	Color Depth
Progressive	4096x2160 DCI 4K & 3840x2160 4K UHD	24 Hz	4:4:4	12 bit
		30 Hz	4:4:4	12 bit
		60 Hz	4:2:2	12 bit
		60 Hz	4:4:4	8 bit
Progressive	2560x1600 WQXGA	60 Hz	4:4:4	8 bit
		1920x1080 FHD 1080p	60 Hz	4:4:4
Interlaced	1920x1080 HD 1080i	30 Hz	4:4:4	12 bit

NOTE: The maximum supported resolution is 4K60 with 4:4:4 color sampling. Custom resolutions are supported at pixel clock rates up to 600 MHz.

Audio

Input Signal Type	HDMI
Output Signal Type	DM Lite
Digital Formats	Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, Dolby Atmos®, DTS®, DTS ES, DTS 96/24, DTS HD® High Res, DTS-HD Master Audio, DTS:X®, LPCM up to 8 channels

Communications

HDMI	HDCP 2.3, EDID, CEC pass-through
DM Lite	HDCP 2.3, EDID pass-through
USB	USB host for one TT-100 series cable caddy (sold separately)

Connectors

HDMI INPUT 1-2	(2) HDMI Type A connectors, female; HDMI digital video/audio inputs; DVI and Dual-Mode DisplayPort™ interface compatible ⁴
DM LITE OUT	(1) 8-pin RJ-45 yellow connector, female, shielded; DM Lite output port for connection to a DM Lite receiver or DMPS Lite™ switcher ^{1,5}
24V 2.5A	(1) 2.1 x 5.5 mm DC power connector; 24VDC power input; PW-2420RU power pack included ³
SERVICE	(1) USB 2.0 Type-A connector, female; Used for firmware loading, configuration management, or as a USB host port for one TT-100 series cable caddy (sold separately); Can also provide up to 5V 500 mA power to a USB powered device
Ground	(1) Chassis ground lug

Controls and Indicators

PWR	(1) LED, indicates that power is being applied to the device. Amber indicates that the device is booting. Green indicates that the device is operational.
AUTO	(1) Push button for enabling or disabling automatic switching of inputs; (1) LED, green indicates that automatic switching of inputs is enabled
SETUP	(1) Push button for Ethernet setup (applicable only when used with a DMPS Lite switcher); (1) LED, red indicates that the SETUP push button is pressed
HDMI INPUT 1-2	(2) Push buttons for manual input selection; (2) LEDs, green indicates that the corresponding input is routed to an output, and amber indicates that a source is detected but is not routed to an output.
DM LITE OUT	(2) LEDs on RJ-45 connector. Green indicates that a DM Lite link is established. Flashing amber indicates non-HDCP video, and solid amber indicates HDCP video.

DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable

Power

Power Pack (Included)	Input: 100-240VAC Output: 24VDC 2.5A Model: PW-2420RU ³
------------------------------	--

Environmental

Temperature	32° to 104°F (0° to 40°C)
Humidity	20% to 90% RH (non-condensing)

Enclosure

Chassis	Metal, black finish, vented top, front, rear, and sides, 2 mounting brackets included
Mounting	Freestanding, surface mountable, or attachment to a single rack rail

Dimensions

Height	1.20 in. (30 mm)
Width	8.52 in. (216 mm)
Depth	5.23 in. (133 mm)

Weight

1.54 lb (0.70 kg)

Compliance

Regulatory Model: M202046002

Intertek® Listed for US and Canada, CE, IC, FCC Part 15 Class A digital device

To search for product certificates, refer to support.crestron.com/app/certificates.

Model

HD-TX-4KZ-201
DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable

Included Accessories

PW-2420RU
Desktop Power Pack, 24 VDC, 2.5 A, 2.1 mm

Available Accessories

For a list of available accessories, visit the [HD-TX-4KZ-201](#) product page.

Notes:

- For DM Lite connections, use Crestron DM-CBL-8G, Crestron DM-CBL-ULTRA, or third-party CAT5e or higher cable. For information about the maximum transmission distance for each cable type, refer to [Online Help Answer ID 1001567](#).

To safeguard against unpredictable environmental electrical noise that may impact performance at resolutions above 1080p, shielded cable and connectors are recommended for all applications and are required when bundling multiple cables in a wire run. Cables are sold separately.
- 4K60 4:4:4 performance and HDR support require the use of HDMI cables and couplers with a minimum TMDS bandwidth of 18 Gbps. If 4K60 4:2:0 or 4K30 4:4:4 performance is acceptable, cables and couplers with a minimum bandwidth of 10.2 Gbps may be used. Bandwidth loss is cumulative; therefore, performance may be reduced when inserting multiple cables and couplers inline.
- When a surface-mountable DM Lite transmitter is paired with a surface-mountable DM Lite receiver, either the power pack included with the transmitter or the receiver can be used to power both devices. A power pack must not be connected to both devices simultaneously.

When a surface-mountable DM Lite transmitter is paired with a wall plate DM Lite receiver, the power pack included with the transmitter is used to power both devices.

When a DM Lite transmitter is paired with a DMPS Lite switcher, the switcher provides power to the DM Lite transmitter. The DM Lite transmitter must not be connected to the included power pack.
- The HDMI input requires an appropriate adapter or interface cable to accommodate a Dual-Mode DisplayPort or DVI signal. CBL-HDI-DVI interface cables are sold separately.
- Examples of supported DM Lite 4K60 4:4:4 receivers are the HD-RX-4KZ-101, HD-RXA-4KZ-101, HD-RXC-4KZ-101, and HD-RXCA-4KZ-101. Supported DM Lite 4K60 4:2:0 receivers are the HD-RX-101-C-E, HD-RXC-101-C-E, HD-RX-201-C-E, HD-RX-101-C-1G-E, and HD-RXC-101-C-1G-E. Supported DMPS Lite switchers are the HD-PS622, HD-PS621, HD-PS402, HD-PS401, and HD-RX-4K-210-C-E (-POE).

DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting www.crestron.com/contact/our-locations for your local contact.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open-source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, .AV Framework, DM Lite, and DMPS Lite are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby, Dolby Atmos, Dolby Digital, and Dolby Vision are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS HD, and DTS:X are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Intertek and the Intertek logo are either trademarks or registered trademarks of Intertek Group in the United States and/or other countries. DisplayPort is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

HDMI

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 06/08/22

DM Lite® 4K60 4:4:4 Transmitter and 2x1 Auto-Switcher for HDMI® Signal Extension over CATx Cable

