

StarDot	SD500BN		
Description	Megapixel Hybrid IP Camera - No H.264 support		
Number of documented streams:	1	Documented Simultaneouse Streams:	Not documented

# **TSX**

### **MJPEG**

Supported:	Yes			
Resolution:	640x480	Camera Quality Setting:	Standard	
Frames per second (fps):	15	Switching Time:	N/A	
URL with user name and password:				
http:// <ip address="">/nph-mjpeg.cgi</ip>				
URL without username and password				
http:// <username>:<password>@<ip address="">/nph-mjpeg.cgi</ip></password></username>				
URL Example				
http://admin:admin@172.30.144.243/nph-mineg.cgi				

## H.264

Supported	No H.264				
Resolution:	N/A	Max Bandwidth	N/A		
Frames per second (fps):	N/A	Switching Time			
I-Frame Setting	N/A				
URL with user name password:	URL with user name password:				
N/A					
URL without user name password:					
N/A					
URL Multicast:					
N/A					
URL Example					
N/A					

StarDot

# SD500BN

# TPMC-V12/15, DGE-2. TPMC-8X-GA

#### **MJPEG**

Supported:	Yes		
Resolution:	1280x720	Camera Quality Setting:	JPEG Quality 50
Frames per second (fps):	N/A - No setting for fps on camera web page	Switching Time:	2-4 sec

URL with user name and password:

http://<username>:<password>@<IP Address>/nph-mjpeg.cgi

URL without username and password

http://<IP Address>/nph-mjpeg.cgi

**URL** Example

http://user:1234@172.30.176.129/nph-mjpeg.cgi

#### H.264

No H.264				
N/A	Max Bandwidth	N/A		
N/A	Switching Time			
N/A				
URL with user name password:				
	N/A N/A	N/A Max Bandwidth N/A Switching Time	N/A Max Bandwidth N/A N/A Switching Time	

URL without user name password:

N/A

**URL Multicast:** 

N/A

**URL** Example

-

StarDot SD500BN

# **TPMC-4SM**

#### **MJPEG**

Supported:	Yes		
Resolution:	320x240	Camera Quality Setting:	Standard
Frames per second (fps):	15	Switching Time:	2~4

URL with user name and password:

http://<IP address>/nph-mjpeg.cgi

URL without username and password

http://<username>:<password>@<IP address>/nph-mjpeg.cgi

**URL** Example

http://admin:admin@172.30.144.243/nph-mjpeg.cgi?fps=15

### H.264

Supported	No H.264			
Resolution:	N/A	Max Bandwidth	N/A	
Frames per second (fps):	N/A	Switching Time		
I-Frame Setting	N/A			
URL with user name password:				
N/A				

N/A

URL without user name password:

N/A

**URL** Multicast:

N/A

**URL** Example

N/A

StarDot	SD500BN		
Crestron App			
MJPEG			
Supported:	Yes		
Resolution:		Camera Quality Setting:	
Frames per second (fps):		Switching Time:	
URL with user name and passwo	ord:		
http:// <username>:<password></password></username>	@ <ip address="">/nph-mjp</ip>	eg.cgi	
URL without username and pass	word		
http:// <ip address="">/nph-mjpeg.</ip>	cgi		
URL Example			
http://user:1234@172.30.176.1	29/nph-mjpeg.cgi		
H.264			
Supported	No H.264		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	

Supported	NO 11.204			
Resolution:	-	Max Bandwidth		
Frames per second (fps):		Switching Time		
I-Frame Setting				
URL with user name password:				
N/A				
URL without user name password:				
-				
URL Multicast:				
-				
URL Example				