

# CL-SPACEBUILDER-GLEX-FT

## SpaceBuilder® System - GLEX-FT

- *Control up to 42 lighting zones*
- *GLEX-FT-56-HC enclosure with hinged cover provides up to 3 module spaces*
- *GLEX-FT-84-HC enclosure with hinged cover provides up to 5 module spaces*
- *Configurable emergency/life safety zones*
- *Flexible dimming control using 2-wire forward phase dimming*
- *Multizone switching*
- *100K/1,000K cycle switching*
- *Scalable using the Ethernet uplink to communicate with external control system*
- *Assembled cabinets are UL508 Listed*
- *120 or 277 VAC*
- *Internal 4-series processor for astronomical time-clock lighting control*

The CL-SPACEBUILDER-GLEX-FT SpaceBuilder® system is a quickly configured and shipped feed-through panel solution that is great for spaces that do not have accessible ceilings such as auditoriums, warehouses, sports venues, and large parking structures. The CL-SPACEBUILDER-GLEX-FT is a quickly configured and shipped feed-through panel solution that supports very large spaces.

### Module Options:

#### Dimming Modules

##### 2-Wire Forward Phase Dimming

Deploy 16 A, 2-wire forward phase dimmed loads using the GLXX-2DIM8. The GLXX-2DIM8 accepts two 20 A inputs that support eight 16 A lighting zones. This module accepts 100–277 VAC power and has a maximum rating of 32 A. Each input can be from a different phase.

##### 4-Wire 0–10 V Dimming

Deploy 16 A, 0–10 V dimmed loads, or 4-wire switched loads, using the GLXP-DIMFLV8-LP. The GLXP-DIMFLV8-LP accepts eight 20 A inputs that support eight 16 A lighting zones. This module accepts 120–277 VAC power.

#### Switching Modules

##### 16-Channel Switching (100,000 Cycle)

Deploy 16 A, 2-wire, 100,000 cycle switched loads using the GLXP-SW16-LP. The GLXP-SW16-LP accepts sixteen 20 A inputs that support sixteen 16 A lighting zones. This module accepts 100–277 VAC power.

##### 12-Channel Switching (1,000,000 Cycle)

Deploy 16 A, 2-wire, 1,000,000 cycle switched loads using the GLXP-SW12-LP. The GLXP-SW12-LP accepts twelve 20 A

inputs that support twelve 16 A lighting zones. This module accepts 100–277 VAC power.

#### Processor Module

The processor module consists of a DIN-AP4 and a DIN-PWS60 which are mounted to a DIN rail. The DIN-AP4 is a Crestron® 4-Series® Control engine that provides fast and powerful control of the lighting system. The DIN-AP4 controls connected modules and supports astronomical time-clock control, 40 Cresnet® control devices, and 50 BACnet™/IP points. The DIN-PWS60 supplies power to the DIN-AP4.

#### Ethernet Uplink Module

The Ethernet uplink module consists of a DIN-CENCN-2-POE and DIN-PWS60 which are mounted to a DIN rail. The DIN-CENCN-2-POE is an Ethernet to Cresnet network bridge that provides scalability to CL-SPACEBUILDER systems. The DIN-CENCN-2-POE receives commands from a DIN-AP4 control system to provide control for the connected modules and to pass commands through to additional CL-SPACEBUILDER systems. The DIN-PWS60 supplies power to the DIN-CENCN-2.

### Options:

#### Assembly

CL-SPACEBUILDER-GLEX-FT systems are assembled in Crestron's UL508 panel shop. The system can also be ordered as individual components that are shipped independently and require on-site assembly.

#### Voltage

The CL-SPACEBUILDER-GLEX-FT is available in 120 or 277 VAC feed through styles.

#### Networking

For easy scalability, CL-SPACEBUILDER-GLEX-FT systems can be configured to use Ethernet or Cresnet communication.



# CL-SPACEBUILDER-GLEX-FT

## SpaceBuilder® System - GLEX-FT

### Specifications

#### Enclosures

**GLEX-FT-56-HC:** Refer to the GLEX-FT-56-HC product page for specifications.

**GLEX-FT-84-HC:** Refer to the GLEX-FT-84-HC product page for specifications.

#### Dimming Modules

**GLXP-DIMFLV8-LP:** Refer to the GLXP-DIMFLV8-LP product page for specifications.

**GLXX-2DIM8:** Refer to the [GLXX-2DIM8](#) product page for specifications.

#### Switching Modules

**GLXP-SW16-LP:** Refer to the GLXP-SW16-LP product page for specifications.

**GLXP-HSW12-LP:** Refer to the GLXP-HSW12-LP product page for specifications.

#### Control System Processor

**DIN-AP4:** Refer to the [DIN-AP4](#) product page for specifications.

#### Ethernet Uplink

**DIN-CENCN-2-POE:** Refer to the [DIN-CENCN-2-POE](#) product page for specifications.

#### Power Supply

**DIN-PWS60:** Refer to the [DIN-PWS60](#) product page for specifications.

#### Construction

**Enclosure:** NEMA 1 metal enclosure suitable for installation in plenum air-handling spaces.

#### Environmental

**Temperature:** 32° to 104°F (0° to 40°C)

**Humidity:** 10% to 90% RH (noncondensing)

### Dimensions

#### GLEX-FT-56-HC:

**Height:** 39-21/32 in. (1,007 mm)

**Width:** 16-1/8 in. (409 mm)

**Depth:** 4-7/16 in. (113 mm)

#### GLEX-FT-84-HC:

**Height:** 62.75 in (1,594 mm)

**Width:** 15.125 in. (384 mm)

**Depth:** 4.94 in. (125 mm)

### Compliance

CE, UL® Listed

CL-SPACEBUILDER-GLEX-FT systems fully assembled in Crestron's UL certified panel shop are UL508 Listed.

To search for product certificates, refer to [support.crestron.com/app/certificates](https://support.crestron.com/app/certificates).

### Assembly

CL-SPACEBUILDER-GLEX-FT systems fully assembled in Crestron's UL certified panel shop are UL508 Listed. The individual components may also be ordered and shipped unassembled, requiring on-site assembly and any applicable certifications and inspections.

### Models and Accessories

#### Available Model

**CL-SPACEBUILDER-GLEX-FT**  
SpaceBuilder® System - GLEX-FT

#### Available Accessories

##### GLEX-FT-56-HC

Green Light Express Enclosure, Feed Through, Hinged Cover, 56 Circuits

##### GLEX-FT-84-HC

Green Light Express Enclosure, Feed Through, Hinged Cover, 84 Circuits

##### GLXP-DIMFLV8-LP

8-Channel 0-10V Dimmer Module, Low Profile

##### GLXX-2DIM8

8-Channel Dimmer Module

##### GLXP-SW16-LP

16-Channel Switch Module, Low Profile

##### GLXP-HSW12-LP

12-Channel High-Inrush Switch Module, Low Profile

# CL-SPACEBUILDER-GLEX-FT

## SpaceBuilder® System - GLEX-FT

### **DIN-AP4**

DIN Rail 4-Series® Automation Processor

### **DIN-PWS60**

DIN Rail 60 Watt Cresnet® Power Supply

### **DIN-CENCN-2-POE**

Ethernet to Cresnet® Bridge with PoE

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or contact us for additional information by visiting [www.crestron.com/contact/our-locations](http://www.crestron.com/contact/our-locations) for your local contact.

The original language version of this document is U.S. English. All other languages are a translation of the original document.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [www.crestron.com/legal/patents](http://www.crestron.com/legal/patents).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, 4-Series, Crestron Green Light, Cresnet and SpaceBuilder are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. BACnet and the BACnet logo are either trademarks or registered trademarks of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.