


# CEN-SWPOE-48

## 48 Port PoE+ Managed Switch



- Class-leading NETGEAR® AV network switch
- Rack-mount 48 port managed switch
- Forty 1000Base-T Gigabit Ethernet ports
- Supports PoE+ (802.3at Type 2) on all Ethernet ports
- Provides up to 30 W per port, 960 W total
- Eight 10 Gigabit Base-X SFP+ ports
- Selectable DM NVX® and DM NAX™ AV-over-IP profiles
- Layer 2 and Layer 3 managed switching functionality
- LLDP (Link Layer Discovery Protocol) support
- 240 Gbps switching fabric (non-blocking)
- Simple-to-use Web browser interface

NETGEAR's class-leading AV network switches are designed to make integration with Crestron AV-over-IP products as simple as possible. The CEN-SWPOE-48 is a 48 port managed Ethernet switch that provides PoE+ from 40 of its ports. The eight 10 Gigabit Base-X SFP+ ports enable use of transceiver modules to connect to a fiber network.

### DM NVX and DM NAX Profiles for Quick Configuration

When configuring a DM NVX or DM NAX system, select the appropriate profile to automatically configure the CEN-SWPOE-48 with the multicast functionality required for AV-over-IP.

### Web Browser Interface

Using a streamlined interface, quickly and completely configure individual ports or assign AV profiles for use with DM NVX or DM NAX systems. An advanced command line interface is also available.

### Eight SFP+ Ports

All SFP+ ports offer 10 Gigabit Base-X connections with support for both multimode and single-mode fiber transceiver modules, such as the [SFP-10G-SR](#).

### Power Over Ethernet+

PoE+ is supplied simultaneously across 40 ports, providing a centralized power source for numerous PoE+ powered devices and eliminating the need for cumbersome power supplies and extra wiring. Up to 30 W is provided per port up to a maximum of 960 W.

## Specifications

### Ethernet

<b>Ports</b>	(40) 10/100/1000Base-T auto-sensing Gigabit Ethernet w/PoE+ (8) 10 Gigabit Base-X SFP+
<b>Network Standards</b>	IEEE 802.3af, 802.3at
<b>MAC Addresses</b>	Up to 16K
<b>Switch Fabric</b>	240 Gbps non-blocking

### Lite Layer 3 Package

<b>Management</b>	Out-of-band; IT Web GUI (main); HTTPs, CLI, Telnet, SSH; SNMP, MIBs, RSPAN; Radius users, TACACS+
<b>IPv4/IPv6 ACL and QoS</b>	Ingress/egress; 1 Kbps shaping, time-based; Single rate policing
<b>IPv4/IPv6 Multicast Filtering</b>	Automated IGMP between switches; IGMPv3 MLDv2 snooping, proxy ASM and SSM; IGMPv1, v2 querier (compatible with v3); Control packet flooding
<b>IPv4/IPv6 Policing and Convergence</b>	Auto-VoIP; Policy-based routing; LLDP-MED; IEEE 1588 PTPv2
<b>IPv4/IPv6 Authentication Security</b>	Successive tiering (DOT1X, MAB, Captive portal); DHCP snooping; Dynamic ARP inspection; IP source guard
<b>IPv4/IPv6 Static Routing</b>	Port, subnet, VLAN routing; Multicast static routes; DHCPv4 server; DHCP relay; Stateful DHCPv6 Server
<b>IPv4/IPv6 Dynamic Routing</b>	IPv4: RIP; IPv4/IPv6: PIM-SM, PIM-DM, SSM
<b>Spanning Tree Green Ethernet</b>	STP, MTP, RSTP; PV(R)STP; BPDU/STRG; EEE 802.3az
<b>VLANs</b>	Static, dynamic, voice, MAC; GVRP/GMRP; Double VLAN mode; Private VLANs

# CEN-SWPOE-48

## 48 Port PoE+ Managed Switch

### Indicators

<b>POWER</b>	(1) green LED, indicates operating power supplied via main power input
<b>FAN</b>	(1) green LED, indicates fan is in operation
<b>PoE MAX</b>	(1) green LED, indicates the unit is supplying the maximum amount of PoE
<b>OOB</b>	(2) green LEDs for Ethernet port, indicates Ethernet link status for out-of-band (service) port
<b>1-40</b>	(2) LEDs per each (40) Ethernet port, left (green) LEDs indicate Ethernet link status for each corresponding port, right (blue) LEDs indicate PoE for each corresponding port
<b>41-48</b>	(1) green LED per SFP+ port, indicates active connection

### Connectors

<b>OOB</b>	(1) 8-wire RJ45, female; 10/100/1000Base-T Ethernet port
<b>CONSOLE</b>	(1) 8-wire RJ45, female
<b>USB-C</b>	USB-C® port, female
<b>100-240V</b>	(1) power connector
<b>USB</b>	USB Type A, female
<b>LED EXT</b>	USB-C® port, female
<b>1-40</b>	(40) 8-wire RJ45, female; 10/100/1000Base-T Ethernet ports and PoE Power Sourcing Equipment (PSE) outputs; Supports IEEE 802.3at Type 2 PoE+ power sourcing from any ports up to the maximum specified power capabilities; Maximum 30 Watts per port, 960 Watts total
<b>41-48</b>	(8) SFP+ ports, female; 10 Gigabit Base-X SFP+

### Power Requirements

<b>Main Power</b>	12 Amps @ 100–240 Volts AC, 50/60Hz
<b>Power Consumption</b>	Max PoE: 1197 W No PoE: 89.2 W Standby: 74.5 W

### Environmental

<b>Temperature</b>	32° to 122° F (0° to 50° C)
<b>Humidity</b>	10% to 90% RH (non-condensing)
<b>Ambient Noise</b>	59 dB at 77° F (25° C)

### Construction

<b>Chassis</b>	Metal, black finish, fan-cooled, vented sides
<b>Mounting</b>	Freestanding or 1U 19-inch rack-mountable with reversible rack ears

### Dimensions

<b>Height</b>	1.7 in. (43.2 mm)
<b>Width</b>	17.32 in. (440 mm)
<b>Depth</b>	15.74 in. (400 mm)

### Weight

13.91 lb (6.31 kg)

### Model

**CEN-SWPOE-48**  
48 Port PoE+ Managed Switch

### Available Accessories

For a list of available accessories, visit the [CEN-SWPOE-48](#) product page.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G, DigitalMedia 8G+, DM, DM 8G, DM 8G+, DM NAX, DM NVX, and DMNet are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. NETGEAR is either a trademark or registered trademark of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. USB-C and USB Type-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2023 Crestron Electronics, Inc.

Rev 01/19/23