

# FSDI8

## 8" Drop-in Ceiling Speaker

- > Full-range 8" ceiling mount loudspeaker
- > Easy drop-in installation for 2x2 and 2x4 ft ceiling grids
- > Fully-enclosed plenum-rated housing
- > Finely-perforated white metal grille
- > Support rail crossbar provided for 2x4 ft applications
- > Includes four seismic attachment points
- > 15 Watts power handling
- > 85 Hz to 18 kHz frequency response
- > 8 Ohm nominal impedance

The Crestron® FSDI8 is a ceiling mount loudspeaker designed for multimedia presentation and speech reinforcement in classrooms and other indoor applications. It features an 8" full-range driver in a damped enclosure. Drop-in simplicity affords fast and easy installation in a typical 2x2 or 2x4 ft suspended ceiling grid.

FSDI8 speakers are priced individually, but must be ordered in pairs.

### SPECIFICATIONS

#### Features & Performance

**Driver:** 8 inch (203 mm) full-range w/secondary high-frequency cone  
**Impedance:** 8 Ohms nominal  
**Frequency Response:** 85 Hz to 18 kHz  
**Sensitivity:** 94 db SPL minimum @ 1W/1m  
**Dispersion:** 100° @ 2kHz (-6dB)  
**Power Handling:** 15 Watts maximum  
**Recommended Amplifier Power:** 5 to 30 Watts

#### Connections

**Input:** 2 conductor red/black flying leads w/wire nuts behind cover;  
Wire entry via conduit knockout or notch

#### Environmental

**Temperature:** 41° to 104°F (5° to 40°C)  
**Humidity:** 10% to 90% RH (non-condensing)  
For indoor use only

#### Enclosure

**Enclosure:** Fully-enclosed, industrial grade steel, plenum-rated (complies with Requirements of Standard UL-2043)  
**Grille:** Finely-perforated metal, textured white finish  
**Mounting:** Designed for 2x2 or 2x4 ft suspended ceiling grid, includes four seismic attachment points and support rail crossbar for 2x4 applications

#### Dimensions

**Height:** 5.00 in (127 mm)



**Width:** 23.82 in (605 mm)  
**Depth:** 23.82 in (605 mm)

#### Weight

12.0 lb (5.5 kg)

### MODELS & ACCESSORIES

#### Available Models

**FSDI8-W-T-EACH:** 8" Drop-in Ceiling Speaker, White Textured, Single (must be ordered in multiples of 2)

#### Available Accessories

**CBL-SPK-P-35:** Speaker Cable, 16AWG, Plenum, 35 ft

#### Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.