

Arecont Vision		AV2255	
Description		Dome Camera ****NOTE: In order to obtain reasonable connection times you MUST issue the following command to the cameras (by typing it in a web browser). This only need to be done once. : http://cam_ip/setreg?page=3®=21&val=3 ****	
Number of documented streams:	2	Documented Simultaneous Streams:	Not documented

TSX

MJPEG

Supported:	Yes		
Resolution:	Half: 1280x720	Camera Quality Setting:	N/A
Frames per second (fps):	15	Switching Time:	N/A
URL with user name and password:			
-			
URL without username and password			
http://<IP address>/mjpeg?res=half&x0=0&y0=0&x1=1280&y1=720&bitrate=1024&fps=10&doublescan=0			
URL Example			
http://172.30.15.42/mjpeg?res=half&x0=0&y0=0&x1=1280&y1=720&bitrate=1024&fps=10&doublescan=0			

H.264

Supported	Some Pixelation		
Resolution:	Half: 1280x720	Max Bandwidth	1024kbps
Frames per second (fps):	15	Switching Time	1~2
I-Frame Setting	N/A		
URL with user name password:			
-			
URL without user name password:			
rtsp://<IP address>/h264.sdp			
URL Multicast:			
-			
URL Example			
rtsp://192.168.1.111/h264.sdp			

TPMC-V12/15, DGE-2. TPMC-8X-GA**MJPEG**

Supported:	Yes		
Resolution:	960x536	Camera Quality Setting:	BAD
Frames per second (fps):	10	Switching Time:	15 sec
URL with user name and password:			
http://<username>:<password>@<IP_address>/mjpeg?res=half&x0=0&y0=0&x1=1920&y1=1080&qp=29&ratelimit=8000&fps=10&doublescan=0&ssn=40941			
URL without username and password			
N/A			
URL Example			
http://admin:admin@172.30.177.25/mjpeg?res=half&x0=0&y0=0&x1=1920&y1=1080&qp=29&ratelimit=8000&fps=10&doublescan=0&ssn=40941			

H.264

Supported	Yes		
Resolution:	960x536	Max Bandwidth	Constant bit rate
Frames per second (fps):	10	Switching Time	15 seconds plus
I-Frame Setting	n/a		
URL with user name password:			
rtsp://<username>:<password>@<IP_address>/h264.sdp?res=half&x0=0&y0=0&x1=1920&y1=1080&qp=29&ratelimit=8000&fps=10&doublescan=0&ssn=40941			
URL without user name password:			
N/A			
URL Multicast:			
N/A			
URL Example			
rtsp://admin:admin@172.30.176.79:554/h264.sdp?res=half&x0=0&y0=0&x1=1920&y1=1080&qp=29&ratelimit=8000&fps=10&doublescan=0&ssn=40941			

TPMC-4SM**MJPEG**

Supported:	Yes		
Resolution:	Half: 1280x720	Camera Quality Setting:	Standard
Frames per second (fps):	15	Switching Time:	3 ~ 10 seconds
URL with user name and password:			
-			
URL without username and password			
http://<IP address>/mjpeg?res=half&x0=0&y0=0&x1=1280&y1=720&bitrate=1024&fps=10&doublescan=0			
URL Example			
-			

H.264

Supported	No		
Resolution:	Half: 320x240	Max Bandwidth	256Kbps
Frames per second (fps):	1	Switching Time	6 ~ 7
I-Frame Setting	N/A		
URL with user name password:			
-			
URL without user name password:			
rtsp://<IP address>/h264.sdp			
URL Multicast:			
-			
URL Example			
-			

Crestron App**MJPEG**

Supported:	Yes		
Resolution:	640x360	Camera Quality Setting:	Low
Frames per second (fps):	7	Switching Time:	2-4 sec
URL with user name and password:			
http://<username>:<password>@<IP_Address>/mjpeg?res=half&x0=0&y0=0&x1=1280&y1=720&qp=29&fps=7&doublescan=0&ssn=40941			
URL without username and password			
N/A			
URL Example			
http://admin:admin@172.30.176.79/mjpeg?res=half&x0=0&y0=0&x1=1280&y1=720&qp=29&fps=7&doublescan=0&ssn=40941			

H.264

Supported	No		
Resolution:	-	Max Bandwidth	
Frames per second (fps):		Switching Time	
I-Frame Setting			
URL with user name password:			
N/A			
URL without user name password:			
-			
URL Multicast:			
-			
URL Example			
-			